SAFETY DATA SHEET

Version # 14

Issue date: 03-11-2013 Revision date: 07-26-2023 Supersedes date: 07-12-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

of the mixture

Chockfast Orange Resin

Registration number

None. Synonyms

SKU# GP101R, GP102R

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Not available. Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

ITW Performance Polymers Company Name

Address Bay 150

Shannon Industrial Estate

Co. Clare Ireland V14 DF82

Contact Person Customer Service Telephone Number 353(61)771500

353(61)471285

customerservice.shannon@itwpp.com **Fmail**

Emergency Phone Number 44(0) 1235 239 670 (24 hours)

1.4. Emergency telephone number

General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

Austria National Poisons

Information Center

+431 406 4343 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Belgium National Poisons

Control Center

070 245 245 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Bulgaria National

Toxicological Information

Center

+359 2 9154 233 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Croatia Poisons Information Center +385 1 2348 342 (Hours of operation not provided. SDS/Product information may

not be available for the Emergency Service.)

Cyprus Poison Center

1401 (Available 24 hours a day. SDS/Product information may not be available

for the Emergency Service.)

Czech Republic National Poisons Information

Center

Control Center

+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Denmark National Poisons

+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Estonia National Poisons Information Center

16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be

available for the Emergency Service.)

Finland National Poison Information Center

(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

France National Poisons Control Center

ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

1.4. Emergency telephone number

Greece Poison Information Centre

(0030) 2107793777 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Hungary National Emergency Phone Number +36-80-201-199 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Iceland Poison Center

(+354) 543 2222 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

113

Latvia Emergency medical

aid

Latvia Poison and Drug Information Center

+371 67042473 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Lithuania Neatidėliotina informacija apsinuodijus

+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Malta Accident and **Emergency Department**

2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Netherlands National Poisons Information Center (NVIC)

NVIC: +31 (0)88 755 8000 (Only for the purpose of informing medical personnel in cases of acute intoxications)

Norway Norwegian Poison Information Center

22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Portugal Poison Center

800 250 250 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Romania Biroul RSI si Informare Toxicologica 021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be

available for the Emergency Service.)

Slovakia National Toxicological Information Center

+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Spain Toxicology Information Service + 34 91 562 04 20 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Sweden National Poison Information Center

112 - and ask for Poison Information (Available 24 hours a day, SDS/Product

information may not be available for the Emergency Service.)

Switzerland Tox Info Suisse

145 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Skin corrosion/irritation Category 2 H315 - Causes skin irritation. Serious eye damage/eye irritation Category 2 H319 - Causes serious eye

irritation.

Skin sensitization H317 - May cause an allergic skin Category 1

reaction.

Environmental hazards

Hazardous to the aquatic environment, Category 2 H411 - Toxic to aquatic life with

long lasting effects. long-term aquatic hazard

2.2. Label elements

Material name: Chockfast Orange Resin

GP101R, GP102R Version #: 14 Revision date: 07-26-2023 Issue date: 03-11-2013

Label according to Regulation (EC) No. 1272/2008 as amended

Austria: F250-Q0HX-M00X-UWGG Belgium: F250-Q0HX-M00X-UWGG Bulgaria: F250-Q0HX-M00X-UWGG Croatia: F250-Q0HX-M00X-UWGG Cyprus: F250-Q0HX-M00X-UWGG

Czech Republic: F250-Q0HX-M00X-UWGG Denmark: F250-Q0HX-M00X-UWGG Estonia: F250-Q0HX-M00X-UWGG EU: F250-Q0HX-M00X-UWGG Finland: F250-Q0HX-M00X-UWGG France: F250-Q0HX-M00X-UWGG Germany: F250-Q0HX-M00X-UWGG Greece: F250-Q0HX-M00X-UWGG Hungary: F250-Q0HX-M00X-UWGG Iceland: F250-Q0HX-M00X-UWGG Ireland: F250-Q0HX-M00X-UWGG Italy: F250-Q0HX-M00X-UWGG Latvia: F250-Q0HX-M00X-UWGG Lithuania: F250-Q0HX-M00X-UWGG Luxembourg: F250-Q0HX-M00X-UWGG Malta: F250-Q0HX-M00X-UWGG Netherlands: F250-Q0HX-M00X-UWGG Norway: F250-Q0HX-M00X-UWGG Poland: F250-Q0HX-M00X-UWGG

Portugal: F250-Q0HX-M00X-UWGG Romania: F250-Q0HX-M00X-UWGG Slovakia: F250-Q0HX-M00X-UWGG Slovenia: F250-Q0HX-M00X-UWGG Spain: F250-Q0HX-M00X-UWGG Sweden: F250-Q0HX-M00X-UWGG

Contains: Crystalline silica, Epoxy Resin: reaction product of bisphenol A and epichlorohydrin (refer to

epichlorohydrin), Limestone

Hazard pictograms



Signal word Warning

Hazard statements

Causes skin irritation. H315

May cause an allergic skin reaction. H317 Causes serious eye irritation. H319 Causes eye irritation.

H320

Toxic to aquatic life with long lasting effects. H411

Precautionary statements

Prevention

P261 Avoid breathing mist/vapors. P264 Wash thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment. P273 Wear eye protection/face protection. P280

Wear protective gloves. P280

Response

IF ON SKIN: Wash with plenty of water. P302 + P352

Not available.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present P305 + P351 + P338

and easy to do. Continue rinsing.

If skin irritation or rash occurs: Ğet medical advice/attention. P333 + P313 If eye irritation persists: Get medical advice/attention. P337 + P313 Take off contaminated clothing and wash it before reuse. P362 + P364 Collect spillage.

P391

Storage Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

Supplemental label information

2.3. Other hazards

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Crystalline silica	30 - 60	14808-60-7 238-878-4	-	-	#
Classification	ո: Carc. 1A;Ի	1350			
Epoxy Resin: reaction product of bisphenol A and epichlorohydrin (refer to epichlorohydrin)	30 - 60	25068-38-6 -	01-2119456619-26-000	-	
Classification	1: Skin Irrit. 2	2;H315, Eye Irrit. 2;H3	319, Skin Sens. 1;H317		
Limestone	5 - < 10	1317-65-3 215-279-6	-	-	
Classification	n: -				

levels

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

Other components below reportable

M: M-factor

vPvB: very persistent and very bioaccumulative substance. PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Union workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The full text for all H-statements is displayed in section 16. Composition comments

< 30

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and

delaved

vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

media Unsuitable extinguishing

Do not use water jet as an extinguisher, as this will spread the fire.

media 5.2. Special hazards arising from the substance or mixture

During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do so without risk. Special fire fighting

procedures

Use standard firefighting procedures and consider the hazards of other involved materials. Specific methods

Material name: Chockfast Orange Resin

SDS FII

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing

appropriate protective clothing. Do not touch or walk through spilled material.

For emergency responders

Keep unnecessary personnel away. Ensure adequate ventilation. Avoid breathing mist/vapors. Local authorities should be advised if significant spillages cannot be contained. Use personal

protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Provide adequate

ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- E2 Hazardous to the Aquatic Environment Chronic (Lower-tier requirements = 200 tons;

Upper-tier requirements = 500 tons)

7.3. Specific end use(s)

Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Components	Туре	Value	Form
Crystalline silica (CAS 14808-60-7)	MAK	0,05 mg/m3	Respirable dust.
Limestone (CAS 1317-65-3)	MAK	5 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
	STEL	20 mg/m3	Inhalable fraction.
		10 mg/m3	Respirable fraction.

Belgium. OEL. Exposure Limit Values to Chemical Substances at Work, Code of Well-being at work, Book VI, Title 1 - Chemical agents, as amended

Components	Туре	Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.
Limestone (CAS 1317-65-3)	TWA	10 mg/m3	

Bulgaria. OEL values of carcinogens and mutagens at work (Reg. 10/2003 on prot. from carcinogens and mutagens at work, Ann. 1), as amended

Components	Туре	Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable fraction and dust

Bulgaria. OELs. Ordinance No 13 on protection of workers against risks of exposure to chemical agents at work, as
amended

Components	Туре	Value	Form
imestone (CAS 1317-65-3)	TWA	1 fibers/cm3	Respirable fraction.
		10 mg/m3	
		10 mg/m3	Inhalable fraction.
Croatia. OELs (GVI). Regulation on Biological Limit Values, Annex I (N		st Exposure to Dangerous Ch	emicals at Work, OELs and
Components	Туре	Value	Form
Crystalline silica (CAS 4808-60-7)	MAC	0,1 mg/m3	
imestone (CAS 1317-65-3)	MAC	4 mg/m3	Respirable dust.
		10 mg/m3	Total dust.
Czech Republic. Occupational exp		ls at work (Decree on protect	ion of health at work,
361/2007, Annex 2, Part A & Annex Components	Type	Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.
_imestone (CAS 1317-65-3)	TWA	10 mg/m3	Dust.
Denmark. Work Environment Autho	ority. Exposure Limits for Sub	ostances & Materials. Annex 2	2
Components	Type	Value	Form
Crystalline silica (CAS 14808-60-7)	TLV	0,3 mg/m3	Total
		0,1 mg/m3	Respirable.
	T1.) /	5 mg/m3	Respirable dust.
imestone (CAS 1317-65-3)	TLV	3 mg/ms	
Limestone (CAS 1317-65-3)	ILV	10 mg/m3	Dust.
Limestone (CAS 1317-65-3)	ILV	-	Dust. Respirable quartz
`		10 mg/m3 0,5 mg/m3	Dust. Respirable quartz fraction.
Estonia. OELs. Occupational Expo		10 mg/m3 0,5 mg/m3	Dust. Respirable quartz fraction.
Estonia. OELs. Occupational Expo Components Crystalline silica (CAS	sure Limits of Hazardous Sub	10 mg/m3 0,5 mg/m3 ostances (Regulation No. 105/	Dust. Respirable quartz fraction. 2001, Annex), as amended
Estonia. OELs. Occupational Expo Components Crystalline silica (CAS 14808-60-7)	sure Limits of Hazardous Sub Type	10 mg/m3 0,5 mg/m3 ostances (Regulation No. 105/ Value	Dust. Respirable quartz fraction. 2001, Annex), as amended Form Fine dust, respiratory
Estonia. OELs. Occupational Expo Components Crystalline silica (CAS 14808-60-7)	sure Limits of Hazardous Sub Type TWA	10 mg/m3 0,5 mg/m3 pstances (Regulation No. 105/Value 0,1 mg/m3	Dust. Respirable quartz fraction. 2001, Annex), as amended Form Fine dust, respiratory fraction
Estonia. OELs. Occupational Expo Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3)	sure Limits of Hazardous Sub Type TWA TWA	10 mg/m3 0,5 mg/m3 estances (Regulation No. 105/ Value 0,1 mg/m3 5 mg/m3 10 mg/m3	Dust. Respirable quartz fraction. 2001, Annex), as amended Form Fine dust, respiratory fraction
Estonia. OELs. Occupational Expo Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) Finland. HTP-arvot, App 3., Binding	sure Limits of Hazardous Sub Type TWA TWA	10 mg/m3 0,5 mg/m3 estances (Regulation No. 105/ Value 0,1 mg/m3 5 mg/m3 10 mg/m3	Dust. Respirable quartz fraction. 2001, Annex), as amended Form Fine dust, respiratory fraction
Estonia. OELs. Occupational Expo Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) Finland. HTP-arvot, App 3., Binding Components Crystalline silica (CAS	sure Limits of Hazardous Sub Type TWA TWA g Limit Values, Social Affairs a	10 mg/m3 0,5 mg/m3 pstances (Regulation No. 105/Value 0,1 mg/m3 5 mg/m3 10 mg/m3 and Ministry of Health	Dust. Respirable quartz fraction. 2001, Annex), as amended Form Fine dust, respiratory fraction Fine dust.
Estonia. OELs. Occupational Expo Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) Finland. HTP-arvot, App 3., Binding Components Crystalline silica (CAS 14808-60-7)	sure Limits of Hazardous Sub Type TWA TWA g Limit Values, Social Affairs a	10 mg/m3 0,5 mg/m3 pstances (Regulation No. 105/Value 0,1 mg/m3 5 mg/m3 10 mg/m3 and Ministry of Health Value	Dust. Respirable quartz fraction. 2001, Annex), as amended Form Fine dust, respiratory fraction Fine dust. Form
Estonia. OELs. Occupational Expo Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) Finland. HTP-arvot, App 3., Binding Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) France. OELs. Occupational Expos	sure Limits of Hazardous Sub Type TWA TWA g Limit Values, Social Affairs a Type TWA TWA	10 mg/m3 0,5 mg/m3 pstances (Regulation No. 105/Value 0,1 mg/m3 5 mg/m3 10 mg/m3 and Ministry of Health Value 0,05 mg/m3 10 mg/m3	Dust. Respirable quartz fraction. 2001, Annex), as amended Form Fine dust, respiratory fraction Fine dust. Form Respirable. Dust.
Estonia. OELs. Occupational Expo Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) Finland. HTP-arvot, App 3., Binding Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) France. OELs. Occupational Expos Components Crystalline silica (CAS 14808-60-7)	sure Limits of Hazardous Sub Type TWA TWA g Limit Values, Social Affairs a Type TWA TWA TWA TWA	10 mg/m3 0,5 mg/m3 pstances (Regulation No. 105/Value 0,1 mg/m3 5 mg/m3 10 mg/m3 and Ministry of Health Value 0,05 mg/m3 10 mg/m3 Art. R.4412-149 of Labor Code	Dust. Respirable quartz fraction. 2001, Annex), as amended Form Fine dust, respiratory fraction Fine dust. Form Respirable. Dust.
Estonia. OELs. Occupational Expo Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) Finland. HTP-arvot, App 3., Binding Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) France. OELs. Occupational Expos Components Crystalline silica (CAS 14808-60-7) France. Threshold Limit Values (VI	sure Limits of Hazardous Sub Type TWA TWA g Limit Values, Social Affairs a Type TWA TWA TWA TWA Sure Limits as Prescribed by A Type VME	10 mg/m3 0,5 mg/m3 pstances (Regulation No. 105/Value 0,1 mg/m3 5 mg/m3 10 mg/m3 and Ministry of Health Value 0,05 mg/m3 10 mg/m3 Art. R.4412-149 of Labor Code Value 0,1 mg/m3	Dust. Respirable quartz fraction. 2001, Annex), as amended Form Fine dust, respiratory fraction Fine dust. Form Respirable. Dust. a samended Form Respirable dust.
Estonia. OELs. Occupational Expo Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) Finland. HTP-arvot, App 3., Binding Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) France. OELs. Occupational Expos Components Crystalline silica (CAS 14808-60-7) France. Threshold Limit Values (VI Components Crystalline silica (CAS	sure Limits of Hazardous Sub Type TWA TWA g Limit Values, Social Affairs a Type TWA TWA TWA TWA TWA Sure Limits as Prescribed by A Type VME	10 mg/m3 0,5 mg/m3 pstances (Regulation No. 105/Value 0,1 mg/m3 5 mg/m3 10 mg/m3 and Ministry of Health Value 0,05 mg/m3 10 mg/m3 Art. R.4412-149 of Labor Code Value 0,1 mg/m3 are to Chemicals in France, IN	Dust. Respirable quartz fraction. 2001, Annex), as amended Form Fine dust, respiratory fraction Fine dust. Form Respirable. Dust. a samended Form Respirable dust. RS ED 984
Estonia. OELs. Occupational Expo Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) Finland. HTP-arvot, App 3., Binding Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) France. OELs. Occupational Expos Components Crystalline silica (CAS 14808-60-7) France. Threshold Limit Values (VI Components Crystalline silica (CAS 14808-60-7) Regulatory status: Regulator	sure Limits of Hazardous Sub Type TWA TWA G Limit Values, Social Affairs a Type TWA TWA TWA TWA Sure Limits as Prescribed by A Type VME LEP) for Occupational Exposu	10 mg/m3 0,5 mg/m3 pstances (Regulation No. 105/Value 0,1 mg/m3 5 mg/m3 10 mg/m3 and Ministry of Health Value 0,05 mg/m3 10 mg/m3 Art. R.4412-149 of Labor Code Value 0,1 mg/m3 are to Chemicals in France, IN Value	Dust. Respirable quartz fraction. 2001, Annex), as amended Form Fine dust, respiratory fraction Fine dust. Form Respirable. Dust. as amended Form Respirable dust. RS ED 984 Form
Estonia. OELs. Occupational Expo Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) Finland. HTP-arvot, App 3., Binding Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) France. OELs. Occupational Expos Components Crystalline silica (CAS 14808-60-7) France. Threshold Limit Values (VI Components Crystalline silica (CAS 14808-60-7) Regulatory status: Regulator	sure Limits of Hazardous Sub Type TWA TWA g Limit Values, Social Affairs a Type TWA TWA TWA TWA Sure Limits as Prescribed by A Type VME LEP) for Occupational Exposuryee VME	10 mg/m3 0,5 mg/m3 pstances (Regulation No. 105/Value 0,1 mg/m3 5 mg/m3 10 mg/m3 and Ministry of Health Value 0,05 mg/m3 10 mg/m3 Art. R.4412-149 of Labor Code Value 0,1 mg/m3 are to Chemicals in France, IN Value	Dust. Respirable quartz fraction. 2001, Annex), as amended Form Fine dust, respiratory fraction Fine dust. Form Respirable. Dust. as amended Form Respirable dust. RS ED 984 Form
Estonia. OELs. Occupational Expo Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) Finland. HTP-arvot, App 3., Binding Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) France. OELs. Occupational Expos Components Crystalline silica (CAS 14808-60-7) France. Threshold Limit Values (VI Components Crystalline silica (CAS 14808-60-7) Regulatory status: Regulator Limestone (CAS 1317-65-3)	sure Limits of Hazardous Sub Type TWA TWA g Limit Values, Social Affairs a Type TWA TWA TWA TWA Sure Limits as Prescribed by A Type VME LEP) for Occupational Exposu Type VME VME Type VME	10 mg/m3 0,5 mg/m3 pstances (Regulation No. 105/Value 0,1 mg/m3 5 mg/m3 10 mg/m3 and Ministry of Health Value 0,05 mg/m3 10 mg/m3 Art. R.4412-149 of Labor Code Value 0,1 mg/m3 ure to Chemicals in France, IN Value 0,1 mg/m3 4 mg/m3	Dust. Respirable quartz fraction. 2001, Annex), as amended Form Fine dust, respiratory fraction Fine dust. Form Respirable. Dust. as amended Form Respirable dust. RS ED 984 Form Respirable fraction.
Estonia. OELs. Occupational Expo Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) Finland. HTP-arvot, App 3., Binding Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) France. OELs. Occupational Expos Components Crystalline silica (CAS 14808-60-7) France. Threshold Limit Values (VI Components Crystalline silica (CAS 14808-60-7) Regulatory status: Regulator Limestone (CAS 1317-65-3) Regulatory status: Regulator	sure Limits of Hazardous Sub Type TWA TWA TWA g Limit Values, Social Affairs a Type TWA TWA TWA TWA TWA Sure Limits as Prescribed by A Type VME LEP) for Occupational Exposu Type VME VME Type VME VME Type VME Type VME VME	10 mg/m3 0,5 mg/m3 pstances (Regulation No. 105/Value 0,1 mg/m3 5 mg/m3 10 mg/m3 and Ministry of Health Value 0,05 mg/m3 10 mg/m3 Art. R.4412-149 of Labor Code Value 0,1 mg/m3 are to Chemicals in France, IN Value 0,1 mg/m3	Dust. Respirable quartz fraction. 2001, Annex), as amended Form Fine dust, respiratory fraction Fine dust. Form Respirable. Dust. a, as amended Form Respirable dust. RS ED 984 Form Respirable fraction.

in the Work Area (DFG), as updated Components	Туре	Value	Form
imestone (CAS 1317-65-3)	TWA	4 mg/m3	Inhalable dust.
Germany. TRGS 900, Limit Values in t Components	he Ambient Air at the Workplace Type	Value	Form
_imestone (CAS 1317-65-3)	AGW	10 mg/m3	Inhalable fraction.
		1,25 mg/m3	Respirable fraction.
Greece. OELs, Presidential Decree No Components	. 307/1986, as amended Type	Value	Form
Limestone (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
,		10 mg/m3	Inhalable
Hungary. OELs. Decree on protection Components	of workers exposed to chemical ag Type	ents (5/2020. (II.6)), <i>I</i> Value	Annex 1&2, as amended Form
Crystalline silica (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.
Limestone (CAS 1317-65-3)	TWA	10 mg/m3	
celand. OELs. Regulation 390/2009 of Components	n Pollution Limits and Measures to Type	Reduce Pollution at Value	the Workplace, as amen Form
Crystalline silica (CAS	TWA	0,3 mg/m3	Total dust.
14808-60-7)		0,1 mg/m3	Respirable dust.
reland. OELVs, Schedules 1 & 2, Cod Components	e of Practice for Chemical Agents a Type	nd Carcinogens Reg Value	ulations Form
Crystalline silica (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.
imestone (CAS 1317-65-3)	TWA	4 mg/m3	Respirable dust.
		10 mg/m3	Total inhalable dust.
taly. OELs (Legislative Decree n.81, 9 Components	April 2008), as amended Type	Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0,025 mg/m3	Respirable fraction.
Latvia. OELs. Occupational Exposure 1), as amended	Limits of Chemical Substances at V	Workplace (Reg. No.	325/ 2007, L.V. 80, Anne
Components	Туре	Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.
Lithuania. OELs. Occupational Expos V-824/A1-389), as amended			
Components	Туре	Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable fraction.
imestone (CAS 1317-65-3)	TWA	5 mg/m3	Respirable fraction.
(10 mg/m3	Inhalable fraction.
(1 1 1 1 1 1)			
_uxembourg. Chemical Substances P 235/2016, as amended			
_uxembourg. Chemical Substances P 235/2016, as amended	Туре	of 14 November 20 Value	16, OJ Memorial A, n° Form
Luxembourg. Chemical Substances P 235/2016, as amended Components Crystalline silica (CAS			
Luxembourg. Chemical Substances P 235/2016, as amended Components Crystalline silica (CAS 14808-60-7) Netherlands. OELs per Annex XIII of Vamended	Type TWA	Value 0,1 mg/m3	Form Respirable dust.
Luxembourg. Chemical Substances P 235/2016, as amended Components Crystalline silica (CAS 14808-60-7) Netherlands. OELs per Annex XIII of V	Type TWA	Value 0,1 mg/m3	Form Respirable dust.

Components	ctors, as amended Type	Value	Form
Crystalline silica (CAS 14808-60-7)	TLV	0,3 mg/m3	Total dust.
11000 00 7)		0,05 mg/m3	Respirable dust.
Poland. Maximum permissible con 1286/2018, Annex 1)	centrations and intensities of	harmful factors in the work e	nvironment (Dz.U.Poz.
Components	Туре	Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable fraction.
Portugal. VLEs. Norm on occupatio Components	onal exposure to chemical ago Type	ents (NP 1796-2014) Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0,025 mg/m3	Respirable fraction.
Romania. OELs. Limit Values of Ch amended)	nemical Agents at Workplace	(Regulation 1.218/2006, M.O 8	45, Annex 1, 3&4, as
Components	Туре	Value	Form
Limestone (CAS 1317-65-3)	TWA	10 mg/m3	Inhalable fraction.
Slovakia. OELs for carcinogens an	d mutagens. Regulation No. 3	356/2006 on carcinogenic and	mutagenic substances,
amended Components	Туре	Value	Form
Crystalline silica (CAS	TWA	0,1 mg/m3	Respirable fraction.
14808-60-7)	Shila assas as Poster Co. 1	tral de la company de la compa	·
Slovakia. OELs. Maximum permiss Annex 1, Table 1, as amended)	ible exposure limits for chem	ical factors in workplace air (Regulation No 355/2006
Components	Туре	Value	
Limestone (CAS 1317-65-3)	TWA	10 mg/m3	
Slovenia. OELs. Occupational Expo	osure Limits of Chemicals at	•	n of Workers from Risks
Slovenia. OELs. Occupational Expo due to Exp. to Chemicals at Work,	osure Limits of Chemicals at Annex I), as amended	Workplace (Reg. on Protectio	
Slovenia. OELs. Occupational Expedue to Exp. to Chemicals at Work, Components	osure Limits of Chemicals at Annex I), as amended Type	Workplace (Reg. on Protectio	Form
Slovenia. OELs. Occupational Expo due to Exp. to Chemicals at Work,	osure Limits of Chemicals at Annex I), as amended	Workplace (Reg. on Protectio Value 10 mg/m3	Form Inhalable fraction.
Slovenia. OELs. Occupational Expedue to Exp. to Chemicals at Work, Components Limestone (CAS 1317-65-3)	osure Limits of Chemicals at Annex I), as amended Type TWA	Workplace (Reg. on Protection Value 10 mg/m3 1,25 mg/m3	Form Inhalable fraction. Respirable fraction.
Slovenia. OELs. Occupational Expedue to Exp. to Chemicals at Work, Components	osure Limits of Chemicals at Annex I), as amended Type TWA	Workplace (Reg. on Protection Value 10 mg/m3 1,25 mg/m3	Form Inhalable fraction. Respirable fraction.
Slovenia. OELs. Occupational Expedue to Exp. to Chemicals at Work, Components Limestone (CAS 1317-65-3) Spain. OELs. INSST, Límites de Ex	osure Limits of Chemicals at Annex I), as amended Type TWA	Workplace (Reg. on Protection Value 10 mg/m3 1,25 mg/m3	Form Inhalable fraction. Respirable fraction.
Slovenia. OELs. Occupational Expedue to Exp. to Chemicals at Work, Components Limestone (CAS 1317-65-3) Spain. OELs. INSST, Límites de Ex (VLAs) Components Crystalline silica (CAS	osure Limits of Chemicals at Annex I), as amended Type TWA posición Profesional Para Ag	Workplace (Reg. on Protection Value 10 mg/m3 1,25 mg/m3 entes Químicos, Table 1-Valo	Form Inhalable fraction. Respirable fraction. res Límites Ambientales
Slovenia. OELs. Occupational Expedue to Exp. to Chemicals at Work, Components Limestone (CAS 1317-65-3) Spain. OELs. INSST, Límites de Ex (VLAs) Components	osure Limits of Chemicals at Annex I), as amended Type TWA posición Profesional Para Ag	Workplace (Reg. on Protection Value 10 mg/m3 1,25 mg/m3 entes Químicos, Table 1-Valo	Form Inhalable fraction. Respirable fraction. res Límites Ambientales Form
Slovenia. OELs. Occupational Expedue to Exp. to Chemicals at Work, Components Limestone (CAS 1317-65-3) Spain. OELs. INSST, Límites de Ex (VLAs) Components Crystalline silica (CAS 14808-60-7)	osure Limits of Chemicals at Annex I), as amended Type TWA posición Profesional Para Ag Type TWA	Workplace (Reg. on Protection Value 10 mg/m3 1,25 mg/m3 entes Químicos, Table 1-Valo Value 0,05 mg/m3	Form Inhalable fraction. Respirable fraction. res Límites Ambientales Form Respirable fraction.
Slovenia. OELs. Occupational Expedue to Exp. to Chemicals at Work, Components Limestone (CAS 1317-65-3) Spain. OELs. INSST, Límites de Ex (VLAs) Components Crystalline silica (CAS 14808-60-7)	osure Limits of Chemicals at Annex I), as amended Type TWA posición Profesional Para Ag Type TWA TWA	Workplace (Reg. on Protection Value 10 mg/m3 1,25 mg/m3 entes Químicos, Table 1-Valo Value 0,05 mg/m3 3 mg/m3 10 mg/m3	Form Inhalable fraction. Respirable fraction. res Límites Ambientales Form Respirable fraction. Respirable fraction. Inhalable fraction.
Slovenia. OELs. Occupational Expedue to Exp. to Chemicals at Work, Components Limestone (CAS 1317-65-3) Spain. OELs. INSST, Límites de Ex (VLAs) Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) Sweden. OELs (Annex 1). Work En	osure Limits of Chemicals at Annex I), as amended Type TWA posición Profesional Para Ag Type TWA TWA	Workplace (Reg. on Protection Value 10 mg/m3 1,25 mg/m3 entes Químicos, Table 1-Valo Value 0,05 mg/m3 3 mg/m3 10 mg/m3	Form Inhalable fraction. Respirable fraction. res Límites Ambientales Form Respirable fraction. Respirable fraction. Inhalable fraction.
Slovenia. OELs. Occupational Expedue to Exp. to Chemicals at Work, Components Limestone (CAS 1317-65-3) Spain. OELs. INSST, Límites de Ex (VLAs) Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) Sweden. OELs (Annex 1). Work Engamended	Type TWA Type TWA Type TWA Type TWA Type TWA Type TWA TWA TWA TWA TWA TWA	Workplace (Reg. on Protection Value 10 mg/m3 1,25 mg/m3 entes Químicos, Table 1-Valo Value 0,05 mg/m3 3 mg/m3 10 mg/m3 cupational Exposure Limit Valo	Form Inhalable fraction. Respirable fraction. res Límites Ambientales Form Respirable fraction. Respirable fraction. Inhalable fraction. Iues (AFS 2018:1), as
Slovenia. OELs. Occupational Expedue to Exp. to Chemicals at Work, Components Limestone (CAS 1317-65-3) Spain. OELs. INSST, Límites de Ex (VLAs) Components Crystalline silica (CAS 1317-65-3) Limestone (CAS 1317-65-3) Sweden. OELs (Annex 1). Work Enamended Components Crystalline silica (CAS	Type TWA TWA TWA TWA TWA TWA TWA TWA	Workplace (Reg. on Protection Value 10 mg/m3 1,25 mg/m3 entes Químicos, Table 1-Valo Value 0,05 mg/m3 3 mg/m3 10 mg/m3 cupational Exposure Limit Value 0,1 mg/m3	Form Inhalable fraction. Respirable fraction. res Límites Ambientales Form Respirable fraction. Respirable fraction. Inhalable fraction. Iues (AFS 2018:1), as Form
Slovenia. OELs. Occupational Expedue to Exp. to Chemicals at Work, Components Limestone (CAS 1317-65-3) Spain. OELs. INSST, Límites de Ex (VLAs) Components Crystalline silica (CAS 1317-65-3) Limestone (CAS 1317-65-3) Sweden. OELs (Annex 1). Work Enamended Components Crystalline silica (CAS 14808-60-7) Switzerland. SUVA Grenzwerte am Components Crystalline silica (CAS 179-179-179-179-179-179-179-179-179-179-	Type TWA TWA TWA TWA TWA TWA TWA TWA	Workplace (Reg. on Protection Value 10 mg/m3 1,25 mg/m3 entes Químicos, Table 1-Valo Value 0,05 mg/m3 3 mg/m3 10 mg/m3 cupational Exposure Limit Value 0,1 mg/m3 Verte	Form Inhalable fraction. Respirable fraction. res Límites Ambientales Form Respirable fraction. Respirable fraction. Inhalable fraction. Iues (AFS 2018:1), as Form Respirable dust.
Slovenia. OELs. Occupational Expedue to Exp. to Chemicals at Work, Components Limestone (CAS 1317-65-3) Spain. OELs. INSST, Límites de Ex (VLAs) Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) Sweden. OELs (Annex 1). Work Enamended Components Crystalline silica (CAS 14808-60-7) Switzerland. SUVA Grenzwerte am	osure Limits of Chemicals at Annex I), as amended Type TWA posición Profesional Para Ag Type TWA TWA TWA vironment Authority (AV), Oct Type TWA Arbeitsplatz: Aktuelle MAK-V Type	Workplace (Reg. on Protection Value 10 mg/m3 1,25 mg/m3 entes Químicos, Table 1-Valo Value 0,05 mg/m3 3 mg/m3 10 mg/m3 cupational Exposure Limit Value 0,1 mg/m3 Verte Value	Form Inhalable fraction. Respirable fraction. res Límites Ambientales Form Respirable fraction. Respirable fraction. Inhalable fraction. Iues (AFS 2018:1), as Form Respirable dust.
Slovenia. OELs. Occupational Expedue to Exp. to Chemicals at Work, Components Limestone (CAS 1317-65-3) Spain. OELs. INSST, Límites de Ex (VLAs) Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) Sweden. OELs (Annex 1). Work Enamended Components Crystalline silica (CAS 14808-60-7) Switzerland. SUVA Grenzwerte am Components Crystalline silica (CAS 14808-60-7)	osure Limits of Chemicals at Annex I), as amended Type TWA posición Profesional Para Ag Type TWA TWA TWA vironment Authority (AV), Occ Type TWA Arbeitsplatz: Aktuelle MAK-V Type TWA	Workplace (Reg. on Protection Value 10 mg/m3 1,25 mg/m3 entes Químicos, Table 1-Valo Value 0,05 mg/m3 3 mg/m3 10 mg/m3 cupational Exposure Limit Value 0,1 mg/m3 Verte Value 0,15 mg/m3	Inhalable fraction. Respirable fraction. res Límites Ambientales Form Respirable fraction. Respirable fraction. Inhalable fraction. Iues (AFS 2018:1), as Form Respirable dust. Form Respirable fraction.
Slovenia. OELs. Occupational Expedue to Exp. to Chemicals at Work, Components Limestone (CAS 1317-65-3) Spain. OELs. INSST, Límites de Ex (VLAs) Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) Sweden. OELs (Annex 1). Work Enamended Components Crystalline silica (CAS 14808-60-7) Switzerland. SUVA Grenzwerte am Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) UK. OELs. Workplace Exposure Lir	Type TWA Type TWA Type TWA Type TWA Type TWA TWA TWA TWA TWA TWA Arbeitsplatz: Aktuelle MAK-W Type TWA TWA TWA TWA TWA TWA TWA TWA	Workplace (Reg. on Protection Value 10 mg/m3 1,25 mg/m3 entes Químicos, Table 1-Valor Value 0,05 mg/m3 10 mg/m3 cupational Exposure Limit Value 0,1 mg/m3 Verte Value 0,15 mg/m3 3 mg/m3 10 mg/m3 10 mg/m3 rth Edition 2020)), Table 1	Inhalable fraction. Respirable fraction. res Límites Ambientales Form Respirable fraction. Respirable fraction. Inhalable fraction. Iues (AFS 2018:1), as Form Respirable dust. Form Respirable fraction.
Slovenia. OELs. Occupational Expedue to Exp. to Chemicals at Work, Components Limestone (CAS 1317-65-3) Spain. OELs. INSST, Límites de Ex (VLAs) Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3) Sweden. OELs (Annex 1). Work Enamended Components Crystalline silica (CAS 14808-60-7) Switzerland. SUVA Grenzwerte am Components Crystalline silica (CAS 14808-60-7) Limestone (CAS 1317-65-3)	osure Limits of Chemicals at Mannex I), as amended Type TWA Posición Profesional Para Ag Type TWA TWA TWA vironment Authority (AV), Oct Type TWA Arbeitsplatz: Aktuelle MAK-V Type TWA TWA TWA	Workplace (Reg. on Protection Value 10 mg/m3 1,25 mg/m3 entes Químicos, Table 1-Valor Value 0,05 mg/m3 10 mg/m3 cupational Exposure Limit Value 0,1 mg/m3 Verte Value 0,15 mg/m3 3 mg/m3 10 mg/m3 10 mg/m3	Form Inhalable fraction. Respirable fraction. res Límites Ambientales Form Respirable fraction. Respirable fraction. Inhalable fraction. Iues (AFS 2018:1), as Form Respirable dust. Form Respirable dust.

Components	Туре	Value	Form
Limestone (CAS 1317-65-3)	TWA	4 mg/m3	Respirable.
		4 mg/m3	Respirable dust.
		10 mg/m3	Inhalable dust.
		10 mg/m3	Inhalable
EU. OELs, Directive 2004/3	37/EC on carcinogen and mutagens fro	3	
•	37/EC on carcinogen and mutagens fro Type	3	
EU. OELs, Directive 2004/3 Components Crystalline silica (CAS 14808-60-7)		om Annex III, Part A, as amei	nded
Components Crystalline silica (CAS	Туре	om Annex III, Part A, as amei Value 0,1 mg/m3	nded Form Respirable fraction and

Bio

Red

Derived no effect levels

(DNELs)

Not available.

Predicted no effect concentrations (PNECs) Not available.

8.2. Exposure controls

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

- Hand protection Wear appropriate chemical resistant gloves.

- Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

In case of insufficient ventilation, wear suitable respiratory equipment. Respiratory protection Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

Environmental exposure

Hygiene measures

controls

Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Liquid. Physical state

Form Liquid. Viscous.

Color Orange. Slight. Odor Not available. Melting point/freezing point >500 °F (>260 °C) **Boiling point or initial boiling**

point and boiling range

Flammability Not applicable.

>400,0 °F (>204,4 °C) Pensky-Martens Closed Cup Flash point

Auto-ignition temperature Not available. **Decomposition temperature** Not available.

pН

Not available. Kinematic viscosity

Solubility

Solubility (water) negligible Partition coefficient Not available.

(n-octanol/water) (log value)

Not available. Vapor pressure

Density and/or relative density

1,64 g/cm3 Density

1,16 g/cm3 estimated

Not available. Vapor density Not available. Particle characteristics

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No relevant additional information available.

9.2.2. Other safety characteristics 1.64 Specific gravity

1,16 estimated

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions

10.3. Possibility of hazardous

No dangerous reaction known under conditions of normal use.

reactions

Contact with incompatible materials. 10.4. Conditions to avoid

10.5. Incompatible materials Strong oxidizing agents.

10.6. Hazardous

decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation No adverse effects due to inhalation are expected.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of Ingestion

occupational exposure.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred **Symptoms**

vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Not known.

Causes skin irritation. Skin corrosion/irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory sensitization Due to partial or complete lack of data the classification is not possible.

Skin sensitization May cause an allergic skin reaction.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Not classified. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline silica (CAS 14808-60-7) 1 Carcinogenic to humans.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -Due to partial or complete lack of data the classification is not possible.

repeated exposure

Aspiration hazard Due to partial or complete lack of data the classification is not possible.

Mixture versus substance information

No information available.

11.2. Information on other hazards

Endocrine disrupting

properties

This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than

0.1% by weight.

Other information Not available.

SECTION 12: Ecological information

Toxic to aquatic life with long lasting effects. Based on available data, the classification criteria are 12.1. Toxicity

not met for hazardous to the aquatic environment, acute hazard.

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Bioconcentration factor (BCF) Not available 12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII.

12.6. Endocrine disrupting

12.7. Other adverse effects

properties

This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

The Waste code should be assigned in discussion between the user, the producer and the waste FU waste code

disposal company.

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow Disposal methods/information

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Special precautions

SECTION 14: Transport information

ADR

LIN3082 14.1. UN number

14.2. UN proper shipping

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin)

14.3. Transport hazard class(es)

Class 9 Subsidiary risk 9 Label(s) 90 Hazard No. (ADR) Tunnel restriction code F 14.4. Packing group Ш

14.5. Environmental hazards No.

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user

RID

14.1. UN number

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin) 14.2. UN proper shipping

name

14.3. Transport hazard class(es) 9 Class

Subsidiary risk

Material name: Chockfast Orange Resin GP101R, GP102R Version #: 14 Revision date: 07-26-2023 Issue date: 03-11-2013 Label(s) 9
14.4. Packing group III
14.5. Environmental hazards No.

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

ADN

14.1. UN number UN3082

14.2. UN proper shipping Environmentally Hazardous Liquid, N.o.s. (Epoxy Resin)

name

14.3. Transport hazard class(es)

Class 9
Subsidiary risk Label(s) 9
14.4. Packing group III
14.5. Environmental hazards No.

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

IATA

14.1. UN number UN3082

14.2. UN proper shipping Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin)

name

14.3. Transport hazard class(es)

Subsidiary risk
14.4. Packing group III

14.5. Environmental hazards Yes
ERG Code 9L

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

Other information

Passenger and cargo Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

14.1. UN number UN3082

14.2. UN proper shipping ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin), MARINE

name POLLUTANT

14.3. Transport hazard class(es)

Class 9
Subsidiary risk 14.4. Packing group III
14.5. Environmental hazards
Marine pollutant Yes
EmS F-A. S-F

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

Bisphenol A/ Epichlorohydrin Resin

14.7. Maritime transport in bulk Not established.

according to IMO instruments

ADN: ADR: IATA: IMDG: RID



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Limestone (CAS 1317-65-3)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

UFI:

Austria: F250-Q0HX-M00X-UWGG Belgium: F250-Q0HX-M00X-UWGG Bulgaria: F250-Q0HX-M00X-UWGG Croatia: F250-Q0HX-M00X-UWGG Cyprus: F250-Q0HX-M00X-UWGG Czech Republic: F250-Q0HX-M00X-UWGG

Denmark: F250-Q0HX-M00X-UWGG Estonia: F250-Q0HX-M00X-UWGG EU: F250-Q0HX-M00X-UWGG Finland: F250-Q0HX-M00X-UWGG France: F250-Q0HX-M00X-UWGG Germany: F250-Q0HX-M00X-UWGG Greece: F250-Q0HX-M00X-UWGG Hungary: F250-Q0HX-M00X-UWGG Iceland: F250-Q0HX-M00X-UWGG Ireland: F250-Q0HX-M00X-UWGG Italy: F250-Q0HX-M00X-UWGG Latvia: F250-Q0HX-M00X-UWGG Lithuania: F250-Q0HX-M00X-UWGG Luxembourg: F250-Q0HX-M00X-UWGG Malta: F250-Q0HX-M00X-UWGG Netherlands: F250-Q0HX-M00X-UWGG Norway: F250-Q0HX-M00X-UWGG Poland: F250-Q0HX-M00X-UWGG Portugal: F250-Q0HX-M00X-UWGG Romania: F250-Q0HX-M00X-UWGG Slovakia: F250-Q0HX-M00X-UWGG

Authorizations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Slovenia: F250-Q0HX-M00X-UWGG Spain: F250-Q0HX-M00X-UWGG Sweden: F250-Q0HX-M00X-UWGG

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Crystalline silica (CAS 14808-60-7)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- E2 Hazardous to the Aquatic Environment Chronic

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Other regulations

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

Young people under 18 years old are not allowed to work with this product according to EU **National regulations**

Directive 94/33/EC on the protection of young people at work, as amended. Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

Contains a substance which is included on the TRGS 905 list of carcinogenic, germ cell mutagenic and reproductive toxic substances

Limestone (CAS 1317-65-3)

Anorganische Faserstäube, soweit nicht erwähnt (ausgenommen

Gipsfasernund Wollastonitfasern)

France regulations

France INRS Table of Occupational Diseases

Crystalline silica (CAS 14808-60-7) Affections consécutives à l'inhalation de poussières minérales

renfermant de la silicecristalline (quartz, cristobalite, tridymite), des silicates cristallins (kaolin, talc), du graphite ou de la houille

Epoxy Resin: reaction product of bisphenol A and

epichlorohydrin (refer to epichlorohydrin)

(CAS 25068-38-6)

Maladies professionnelles provoquées par les résines

époxydiques et leurs constituants 51

Product registration number

UFI: F250-Q0HX-M00X-UWGG **Austria Belgium** UFI: F250-Q0HX-M00X-UWGG Czech Republic UFI: F250-Q0HX-M00X-UWGG UFI: F250-Q0HX-M00X-UWGG **Denmark** UFI: F250-Q0HX-M00X-UWGG **European Union Finland** UFI: F250-Q0HX-M00X-UWGG UFI: F250-Q0HX-M00X-UWGG **France** Germany UFI: F250-Q0HX-M00X-UWGG UFI: F250-Q0HX-M00X-UWGG Greece UFI: F250-Q0HX-M00X-UWGG Hungary Italy UFI: F250-Q0HX-M00X-UWGG **Netherlands** UFI: F250-Q0HX-M00X-UWGG Norway UFI: F250-Q0HX-M00X-UWGG **Poland** UFI: F250-Q0HX-M00X-UWGG **Portugal** UFI: F250-Q0HX-M00X-UWGG Slovakia UFI: F250-Q0HX-M00X-UWGG Slovenia UFI: F250-Q0HX-M00X-UWGG UFI: F250-Q0HX-M00X-UWGG **Spain** UFI: F250-Q0HX-M00X-UWGG Sweden UFI: F250-Q0HX-M00X-UWGG **Switzerland**

15.2. Chemical safety

No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

List of abbreviations

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization. IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value.

vPvB: Very persistent and very bioaccumulative.

References

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements, which are not written out in full

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H350 May cause cancer.

Revision information Training information Disclaimer

under sections 2 to 15

Physical & Chemical Properties: Multiple Properties Follow training instructions when handling this material.

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Material name: Chockfast Orange Resin

SDS FIL 15 / 15