SAFETY DATA SHEET

Version #: 12 Issue date: 03-11-2013 Revision date: 07-26-2023 Supersedes date: 07-12-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

	1 5 6
1.1. Product identifier Trade name or designation of the mixture	Chockfast Gray Resin
Registration number	
Synonyms	None.
SKU#	GP103R
1.2. Relevant identified uses of the Identified uses	he substance or mixture and uses advised against Not available.
Uses advised against	None known.
1.3. Details of the supplier of the	safety data sheet
Company Name	ITW Performance Polymers
Address	Bay 150
	Shannon Industrial Estate
	Co. Clare
	Ireland
	V14 DF82
Contact Person	Customer Service
Telephone Number	353(61)771500
	353(61)471285
Email	customerservice.shannon@itwpp.com
Emergency Phone Number	44(0) 1235 239 670 (24 hours)
1.4. Emergency telephone numb General in EU	er 112 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Austria National Poisons Information Center	+431 406 4343 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Belgium National Poisons Control Center	070 245 245 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Bulgaria National Toxicological Information Center	+359 2 9154 233 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Croatia Poisons Information Center	+385 1 2348 342 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
Cyprus Poison Center	1401 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Czech Republic National Poisons Information Center	+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
Denmark National Poisons Control Center	+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Estonia National Poisons Information Center	16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be available for the Emergency Service.)
Finland National Poison Information Center	(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
France National Poisons Control Center	ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

1.4. [1.4. Emergency telephone number		
	Greece Poison Information Centre	(0030) 2107793777 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)	
	Hungary National Emergency Phone Number	+36-80-201-199 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)	
I	Iceland Poison Center	(+354) 543 2222 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)	
	Latvia Emergency medical aid	113	
	Latvia Poison and Drug Information Center	+371 67042473 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)	
	Lithuania Neatidėliotina informacija apsinuodijus	+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)	
-	Malta Accident and Emergency Department	2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)	
I	Netherlands National Poisons Information Center (NVIC)	NVIC: +31 (0)88 755 8000 (Only for the purpose of informing medical personnel in cases of acute intoxications)	
	Norway Norwegian Poison Information Center	22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)	
I	Portugal Poison Center	800 250 250 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)	
-	Romania Biroul RSI si Informare Toxicologica	021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be available for the Emergency Service.)	
-	Slovakia National Toxicological Information Center	+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)	
	Spain Toxicology Information Service	+ 34 91 562 04 20 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)	
	Sweden National Poison Information Center	112 - and ask for Poison Information (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)	
	Switzerland Tox Info Suisse	145 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
Skin sensitization	Category 1	H317 - May cause an allergic skin reaction.
Environmental hazards Hazardous to the aquatic environment, long-term aquatic hazard	Category 2	H411 - Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended UFI:

Austria: H050-60UJ-A00F-6JWE Belgium: H050-60UJ-A00F-6JWE Bulgaria: H050-60UJ-A00F-6JWE Croatia: H050-60UJ-A00F-6JWE Cyprus: H050-60UJ-A00F-6JWE Czech Republic: H050-60UJ-A00F-6JWE Denmark: H050-60UJ-A00F-6JWE Estonia: H050-60UJ-A00F-6JWE EU: H050-60UJ-A00F-6JWE Finland: H050-60UJ-A00F-6JWE France: H050-60UJ-A00F-6JWE Germany: H050-60UJ-A00F-6JWE Greece: H050-60UJ-A00F-6JWE Hungary: H050-60UJ-A00F-6JWE Iceland: H050-60UJ-A00F-6JWE Ireland: H050-60UJ-A00F-6JWE Italy: H050-60UJ-A00F-6JWE Latvia: H050-60UJ-A00F-6JWE Lithuania: H050-60UJ-A00F-6JWE Luxembourg: H050-60UJ-A00F-6JWE Malta: H050-60UJ-A00F-6JWE Netherlands: H050-60UJ-A00F-6JWE Norway: H050-60UJ-A00F-6JWE Poland: H050-60UJ-A00F-6JWE Portugal: H050-60UJ-A00F-6JWE Romania: H050-60UJ-A00F-6JWE Slovakia: H050-60UJ-A00F-6JWE Slovenia: H050-60UJ-A00F-6JWE Spain: H050-60UJ-A00F-6JWE Sweden: H050-60UJ-A00F-6JWE

Contains:

Butyrolactone, CARBON BLACK, Crystalline SiO2 (Quartz), Epoxy Resin: Reaction product of bisphenol A and epichlorohydrin (refer to epichlorohydrin), titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]



Signal word

Hazard statements

Hazard pictograms

H315 H317 H319 H411 Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention	
P261	Avoid breathing mist/vapors.
P264	Wash thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear eye protection/face protection.
P280	Wear protective gloves.
Response	
P302 + P352	IF ON SKIN: Wash with plenty of water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
Storage	Not available.
Disposal	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information None.

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information					
Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Crystalline SiO2 (Quartz)	30 - 60	14808-60-7 238-878-4	-	-	#
Classif	ication: Carc. 1A;	H350			
Epoxy Resin: Reaction produc bisphenol A and epichlorohydr (refer to epichlorohydrin)		25068-38-6 -	01-2119456619-26-0000	-	
Classif	ication: Skin Irrit.	2;H315, Eye Irrit. 2;H	319, Skin Sens. 1;H317		
Butyrolactone	1 - 5	96-48-0 202-509-5	-	-	
Classif	ication: Acute To: 2,680000	x. 4;H302;(ATE: 1540 0000000002 mg/l), Ey	mg/kg bw), Acute Tox. 3;H3 /e Irrit. 2;H319	31;(ATE:	
titanium dioxide [in powder for containing 1 % or more of part with aerodynamic diameter <	icles	13463-67-7 236-675-5	01-2119489379-17-0000	022-006-002	
Classif	ication: Carc. 2;H	351			
CARBON BLACK	0,1 - 1	1333-86-4 215-609-9	-	-	
Classif	ication: Carc. 2;H	351			
Other components below repo levels	rtable < 25				
vPvB: very persistent and very PBT: persistent, bioaccumulat #: This substance has been as All concentrations are in perce Composition comments	ive and toxic subs ssigned Union wor int by weight unles Hazardous Mate secret exemptior	tance. kplace exposure limit(ss ingredient is a gas. rials Information Revio n. A CLAIM FOR EXE		t has been grant M DISCLOSING	ted a trade THE IDENTITY
SECTION 4: First aid meas					0, 2010.
		ical paraappal ara aw	are of the material(s) involve		autiona ta
General information			ed clothing before reuse.	a, and take preca	
4.1. Description of first aid meas	ures				
Inhalation	Move to fresh air	. Call a physician if sy	mptoms develop or persist.		
Skin contact	eczema or other		liately and wash skin with soa medical attention and take al		
Eye contact			vater for at least 15 minutes. ng. Get medical attention if ir		
Ingestion	Rinse mouth. Ge	et medical attention if s	symptoms occur.		
4.2. Most important symptoms and effects, both acute and delayed			nclude stinging, tearing, redn ess and pain. May cause an a		
4.3. Indication of any immediate medical attention and special treatment needed	Provide general Symptoms may l		and treat symptomatically. Ke	ep victim under	observation.
SECTION 5: Firefighting n	neasures				
General fire hazards	No unusual fire o	or explosion hazards r	noted.		
5.1. Extinguishing media					

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Suitable extinguishing

media

Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from the substance or mixture	During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Special fire fighting procedures	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
SECTION C. Assidental ra	

SECTION 6: Accidental release measures

6.1. Personal precautions, protection	ctive equipment and emergency procedures
For non-emergency personnel	Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.
For emergency responders	Keep unnecessary personnel away. Ensure adequate ventilation. Avoid breathing mist/vapors. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.
6.2. Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
6.3. Methods and material for	Prevent entry into waterways, sewer, basements or confined areas.
containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use.
6.4. Reference to other sections	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.
SECTION 7: Handling and	storage
7.1. Precautions for safe handling	Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
7.2. Conditions for safe storage, including any	Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).
incompatibilities	Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended
	ANNEX 1, PART 1 Categories of dangerous substances Hazard categories in accordance with Regulation (EC) No 1272/2008 - E2 Hazardous to the Aquatic Environment Chronic (Lower-tier requirements = 200 tons; Upper-tier requirements = 500 tons)
7.3. Specific end use(s)	Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBI. II, no. 184/2001, as amended

Components	Туре	Value	Form
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	MAK	0,05 mg/m3	Respirable dust.
Magnesium silicate hydrate (CAS 14807-96-6)	МАК	2 mg/m3	Respirable fraction.
	STEL	20 mg/m3	Inhalable fraction.
		10 mg/m3	Respirable fraction.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 µm] (CAS 13463-67-7)	МАК	5 mg/m3	Respirable dust.

STEL 10 mg/m3 Respirable dust. Belgium. OEL. Exposure Limit Values to Chemical Substances at Work, Code of Well-being at work, Book VI, Title 1 -

	•	
Chemical	agents, as amended	

Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	TWA	3 mg/m3	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	TWA	10 mg/m3	

Bulgaria. OEL values of carcinogens and mutagens at work (Reg. 10/2003 on prot. from carcinogens and mutagens at work, Ann. 1), as amended

Components	Туре	Value	Form
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable fraction and dust

Bulgaria. OELs. Ordinance No 13 on protection of workers against risks of exposure to chemical agents at work, as amended

Components	Туре	Value	Form
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	1 fibers/cm3	Respirable fraction.
		6 mg/m3	Inhalable fraction.
		3 mg/m3	Respirable fraction.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 µm] (CAS 13463-67-7)	TWA	10 mg/m3	Respirable dust.

Croatia. OELs (GVI). Regulation on Protection of Workers against Exposure to Dangerous Chemicals at Work, OELs and Biological Limit Values, Annex I (NN 91/2018), as amended

Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	MAC	3,5 mg/m3	
	STEL	7 mg/m3	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	MAC	0,1 mg/m3	
Magnesium silicate hydrate (CAS 14807-96-6)	MAC	1 mg/m3	Respirable dust.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 µm] (CAS 13463-67-7)	MAC	4 mg/m3	Respirable dust.
,		10 mg/m3	Total dust.

Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended Components Type Value

components	туре	Value	
CARBON BLACK (CAS 1333-86-4)	TWA	3,5 mg/m3	
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	706 part/cm3	
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	TWA	10 mg/m3	

	Туре	Value	Form
ARBON BLACK (CAS 333-86-4)	TWA	10 mg/m3	Dust.
rystalline SiO2 (Quartz) CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.
agnesium silicate hydrate CAS 14807-96-6)	TWA	2 mg/m3	Respirable dust.
		10 mg/m3	Total dust.
enmark. Work Environment Auth omponents	ority. Exposure Limits for Su Type	bstances & Materials, Annex 2 Value	Form
ARBON BLACK (CAS 333-86-4)	TLV	3,5 mg/m3	
rystalline SiO2 (Quartz) CAS 14808-60-7)	TLV	0,3 mg/m3	Total
		0,1 mg/m3	Respirable.
agnesium silicate hydrate CAS 14807-96-6)	TLV	0,003 fibers/cm3	Fiber.
canium dioxide [in powder orm containing 1 % or ore of particles with erodynamic diameter ≤ 10 m] (CAS 13463-67-7)	TLV	6 mg/m3	
stonia. OELs. Occupational Expo omponents	osure Limits of Hazardous Su Type	bstances (Regulation No. 105/20 Value	001, Annex), as amend Form
rystalline SiO2 (Quartz) CAS 14808-60-7)	TWA	0,1 mg/m3	Fine dust, respiratory fraction
tanium dioxide [in powder orm containing 1 % or nore of particles with erodynamic diameter ≤ 10 m] (CAS 13463-67-7)	TWA	5 mg/m3	
• • • • • •			
nland. HTP-arvot, App 3., Bindin	g Limit Values, Social Affairs Type	and Ministry of Health Value	Form
nland. HTP-arvot, App 3., Bindin omponents utyrolactone (CAS			Form
nland. HTP-arvot, App 3., Bindin omponents utyrolactone (CAS	Туре	Value	Form
nland. HTP-arvot, App 3., Bindin omponents utyrolactone (CAS	Туре	Value70 mg/m3	Form
nland. HTP-arvot, App 3., Bindin omponents utyrolactone (CAS	Type STEL	Value 70 mg/m3 250 ppm	Form
Inland. HTP-arvot, App 3., Bindin omponents utyrolactone (CAS 6-48-0) ARBON BLACK (CAS	Type STEL	Value 70 mg/m3 250 ppm 14 mg/m3	Form
inland. HTP-arvot, App 3., Bindin omponents utyrolactone (CAS 6-48-0) ARBON BLACK (CAS	Type STEL TWA	Value 70 mg/m3 250 ppm 14 mg/m3 50 ppm	Form
inland. HTP-arvot, App 3., Bindin omponents utyrolactone (CAS 5-48-0) ARBON BLACK (CAS 333-86-4) rystalline SiO2 (Quartz)	Type STEL TWA STEL	Value 70 mg/m3 250 ppm 14 mg/m3 50 ppm 7 mg/m3	Form Respirable.
inland. HTP-arvot, App 3., Bindin omponents utyrolactone (CAS 6-48-0) ARBON BLACK (CAS 333-86-4) rystalline SiO2 (Quartz) CAS 14808-60-7) lagnesium silicate hydrate	Type STEL TWA STEL TWA	Value 70 mg/m3 250 ppm 14 mg/m3 50 ppm 7 mg/m3 3,5 mg/m3 0,05 mg/m3 2 mg/m3	Respirable. Inhalable dust.
inland. HTP-arvot, App 3., Bindin omponents utyrolactone (CAS 3-48-0) ARBON BLACK (CAS 333-86-4) rystalline SiO2 (Quartz) CAS 14808-60-7) agnesium silicate hydrate	Type STEL TWA STEL TWA TWA	Value 70 mg/m3 250 ppm 14 mg/m3 50 ppm 7 mg/m3 3,5 mg/m3 0,05 mg/m3 2 mg/m3 1 mg/m3	Respirable.
Inland. HTP-arvot, App 3., Bindin omponents utyrolactone (CAS 5-48-0) ARBON BLACK (CAS 333-86-4) rystalline SiO2 (Quartz) CAS 14808-60-7) agnesium silicate hydrate CAS 14807-96-6) anium dioxide [in powder rm containing 1 % or ore of particles with erodynamic diameter ≤ 10	Type STEL TWA STEL TWA TWA	Value 70 mg/m3 250 ppm 14 mg/m3 50 ppm 7 mg/m3 3,5 mg/m3 0,05 mg/m3 2 mg/m3	Respirable. Inhalable dust.
inland. HTP-arvot, App 3., Bindin components iutyrolactone (CAS 6-48-0) CARBON BLACK (CAS 333-86-4) Crystalline SiO2 (Quartz) CAS 14808-60-7) Magnesium silicate hydrate CAS 14807-96-6) tanium dioxide [in powder orm containing 1 % or hore of particles with erodynamic diameter ≤ 10 m] (CAS 13463-67-7) france. OELs. Occupational Expon components	Type STEL TWA STEL TWA TWA TWA TWA	Value 70 mg/m3 250 ppm 14 mg/m3 50 ppm 7 mg/m3 3,5 mg/m3 0,05 mg/m3 2 mg/m3 1 mg/m3 10 mg/m3	Respirable. Inhalable dust. Respirable. Dust.

Components	/alues (VLEP) for Occupational Exposเ Type	Value	Form
CARBON BLACK (CAS 1333-86-4)	VME	3,5 mg/m3	
Regulatory status:	Indicative limit (VL)		
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	VME	0,1 mg/m3	Respirable fraction.
Regulatory status:	Regulatory binding (VRC)		
Magnesium silicate hydrate (CAS 14807-96-6)	e VME	4 mg/m3	Total dust.
Regulatory status:	Regulatory binding (VRC)		
		0,9 mg/m3	Respirable dust.
Regulatory status:	Regulatory binding (VRC)		
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7))	10 mg/m3	
Regulatory status:	Indicative limit (VL)		

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG), as updated

Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	TWA	4 mg/m3	Inhalable dust.
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	4 mg/m3	Inhalable dust.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	TWA	0,3 mg/m3	Respirable fraction.

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	AGW	10 mg/m3	Inhalable fraction.
		1,25 mg/m3	Respirable fraction.
Magnesium silicate hydrate (CAS 14807-96-6)	AGW	10 mg/m3	Inhalable fraction.
		1,25 mg/m3	Respirable fraction.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	AGW	10 mg/m3	Inhalable fraction.
		1,25 mg/m3	Respirable fraction.
Greece. OELs, Presidential Decre	e No. 307/1986, as amended		

Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	STEL	7 mg/m3	
	TWA	3,5 mg/m3	
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable.
		10 mg/m3	Inhalable
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Inhalable

Hungary. OELs. Decree on protection of workers exposed to chemical agents (5/2020. (II.6)), Annex 1&2, as amendedComponentsTypeValueForm

Components	туре	value	FOIII	
CARBON BLACK (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable dust.	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.	
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable dust.	

Iceland. OELs. Regulation 390/2009 on Pollution Limits and Measures to Reduce Pollution at the Workplace, as amended Components Type Value Form

	.) -		
CARBON BLACK (CAS 1333-86-4)	TWA	3,5 mg/m3	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,3 mg/m3	Total dust.
		0,1 mg/m3	Respirable dust.
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	0,3 fibers/cm3	Fiber.
		5 mg/m3	Respirable dust.
		10 mg/m3	Total dust.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	TWA	6 mg/m3	

Ireland. OELVs, Schedules 1 & 2, Code of Practice for Chemical Agents and Carcinogens Regulations

Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	10 mg/m3	Total inhalable dust.
		0,8 mg/m3	Respirable dust.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	TWA	4 mg/m3	Respirable dust.

10 mg/m3

Total inhalable dust.

Italy. OELs (Legislative Decree n.81, 9 April 2008), as amended

Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,025 mg/m3	Respirable fraction.
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 µm] (CAS 13463-67-7)	TWA	2,5 mg/m3	Respirable finescale particles
		0,2 mg/m3	Respirable nanoscale particles

Latvia. OELs. Occupational Exposure Limits of Chemical Substances at Workplace (Reg. No. 325/ 2007, L.V. 80, Annex 1). as amended

Components	Туре	Value	Form
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.

Latvia. OELs. Occupational Exposure Limits of Chemical Substances at Workplace (Reg. No. 325/ 2007, L.V. 80, Annex 1), as amended

Components	Туре	Value	Form
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	TWA	10 mg/m3	

Lithuania. OELs. Occupational Exposure Limit Values for Chemical Substances (Hygiene Norm HN 23:2011; Order No. V-824/A1-389), as amended

Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	TWA	5 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable fraction.
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Inhalable fraction.
		1 mg/m3	Respirable fraction.
itanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 um] (CAS 13463-67-7)	TWA	5 mg/m3	
_uxembourg. Chemical Substanco 235/2016, as amended	es Prohibited at Work (Annex	III), G.D.R. of 14 November 20	16, OJ Memorial A, n °
Components	Туре	Value	Form
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.
Netherlands. OELs per Annex XIII amended	of Working Conditions Regu	lation (Staatscourant no. 252, 2	29 December 2006), as
Components	Туре	Value	Form
Crystalline SiO2 (Quartz) CAS 14808-60-7)	TWA	0,075 mg/m3	Respirable dust.
Magnesium silicate hydrate CAS 14807-96-6)	TWA	0,25 mg/m3	Respirable dust.
Norway. Regulation No. 1358 on M Infection Groups for Biological Fa		Physical and Chemical Facto	rs in Work Environment a
Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	TLV	3,5 mg/m3	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TLV	0,3 mg/m3	Total dust.
		0,05 mg/m3	Respirable dust.
Magnesium silicate hydrate CAS 14807-96-6)	TLV	6 mg/m3	Total dust.
		2 mg/m3	Respirable dust.
titanium dioxide [in powder form containing 1 % or more of particles with	TLV	5 mg/m3	

more of particles with aerodynamic diameter ≤ 10

µm] (ČAS 13463-67-7)

Poland. Maximum permissible concentrations and intensities of harmful factors in the work environment (Dz.U.Poz. 1286/2018, Annex 1)

Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	TWA	4 mg/m3	Inhalable fraction.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable fraction.
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	4 mg/m3	Inhalable fraction.

1286/2018, Annex 1) Components	Туре	Value	Form
		1 mg/m3	Respirable fraction.
itanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 um] (CAS 13463-67-7)	STEL	30 mg/m3	
	TWA	10 mg/m3	Inhalable fraction.
Portugal. VLEs. Norm on occupati Components	onal exposure to chemical ag Type	jents (NP 1796-2014) Value	Form
CARBON BLACK (CAS 1333-86-4)	TWA	3 mg/m3	Fume.
Crystalline SiO2 (Quartz) CAS 14808-60-7)	TWA	0,025 mg/m3	Respirable fraction.
/lagnesium silicate hydrate CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
itanium dioxide [in powder orm containing 1 % or nore of particles with ierodynamic diameter ≤ 10 im] (CAS 13463-67-7)	TWA	10 mg/m3	
Romania. OELs. Limit Values of C Imended)	hemical Agents at Workplace	(Regulation 1.218/2006, M.O 8	45, Annex 1, 3&4, as
Components	Туре	Value	Form
/agnesium silicate hydrate CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
itanium dioxide [in powder orm containing 1 % or nore of particles with aerodynamic diameter ≤ 10 um] (CAS 13463-67-7)	STEL	15 mg/m3	
	TWA	10 mg/m3	
lovakia. OELs for carcinogens a	nd mutagens. Regulation No.	356/2006 on carcinogenic and	mutagenic substances
imended Components	Туре	Value	Form
Crystalline SiO2 (Quartz)	TWA	0,1 mg/m3	Respirable fraction.
CAS 14808-60-7)			
Slovakia. OELs. Maximum permis Annex 1, Table 1, as amended)	sible exposure limits for chen	nical factors in workplace air (i	Regulation No 355/2006
Components	Туре	Value	Form
ARBON BLACK (CAS 333-86-4)	TWA	2 mg/m3	
/lagnesium silicate hydrate CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
		2 mg/m3	Respirable fraction.
		10 mg/m3	Total
tanium dioxide [in powder orm containing 1 % or nore of particles with erodynamic diameter ≤ 10 m] (CAS 13463-67-7)	TWA	5 mg/m3	
Slovenia. OELs. Occupational Exp		Workplace (Reg. on Protection	n of Workers from Risk
due to Exp. to Chemicals at Work, Components	Annex I), as amended Type	Value	Form
CARBON BLACK (CAS	TWA	10 mg/m3	Inhalable fraction.
1333-86-4)		10 119/110	

CARBON BLACK (CAS 1333-86-4)	TWA	10 mg/m3	Inhalable fraction.
		1,25 mg/m3	Respirable fraction.
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	10 mg/m3	Inhalable fraction.

Components	Туре	Value	Form
		1,25 mg/m3	Respirable fraction.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 µm] (CAS 13463-67-7)	TWA	10 mg/m3	Inhalable fraction.
		1,25 mg/m3	Respirable fraction.

Spain. OELs. INSST, Límites de Exposición Profesional Para Agentes Químicos, Table 1-Valores Límites Ambientales (VLAs)

Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	TWA	3,5 mg/m3	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,05 mg/m3	Respirable fraction.
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	TWA	10 mg/m3	

Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended

Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	TWA	5 mg/m3	Inhalable dusts and mists.
		1 mg/m3	Inhalable dust.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Total dust.
		1 mg/m3	Respirable dust.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	TWA	5 mg/m3	Total dust.

Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle MAK-Werte

Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	TWA	3 mg/m3	Respirable dust.
		10 mg/m3	Inhalable dust.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,15 mg/m3	Respirable fraction.
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	3 mg/m3	Respirable fraction.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 µm] (CAS 13463-67-7)	TWA	3 mg/m3	Respirable dust.

UK. OELs. Workplace Exposure Limits (WELs) (EH40/2005 (Fourth Edition 2020)), Table 1

Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	STEL	7 mg/m3	
	TWA	3,5 mg/m3	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable.

Components	Туре	rth Edition 2020)), Table 1 Value	Form
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	1 mg/m3	Respirable dust.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 µm] (CAS 13463-67-7)	TWA	4 mg/m3	Respirable.
		10 mg/m3	Inhalable
EU. OELs, Directive 2004/37 Components	7/EC on carcinogen and mutagens fr Type	om Annex III, Part A, as amen Value	ded Form
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable fraction and dust
ological limit values	No biological exposure limits noted for	or the ingredient(s).	
commended monitoring	Follow standard monitoring procedur	es.	
rived no effect levels NELs)	Not available.		
edicted no effect ncentrations (PNECs)	Not available.		
posure guidelines			
Finland Exposure Limit Val	ues: Skin designation		
Butyrolactone (CAS 96-4 Germany DFG MAK (adviso	,	be absorbed through the skin.	
Butyrolactone (CAS 96-4	8-0) Can	be absorbed through the skin.	
. Exposure controls			
propriate engineering ntrols	Good general ventilation should be u applicable, use process enclosures, maintain airborne levels below recon established, maintain airborne levels shower.	local exhaust ventilation, or othe nmended exposure limits. If exp	er engineering controls to osure limits have not been
lividual protection measures,	such as personal protective equipm	ient	
General information	Use personal protective equipment a according to the CEN standards and equipment.		
Eye/face protection	Wear safety glasses with side shields	s (or goggles). Face shield is re	commended.
Skin protection			
- Hand protection	Wear appropriate chemical resistant	gloves.	
- Other	Wear appropriate chemical resistant	clothing. Use of an impervious	apron is recommended.
Respiratory protection	In case of insufficient ventilation, wea	ar suitable respiratory equipmer	nt.
Thermal hazards	Wear appropriate thermal protective	clothing, when necessary.	
giene measures	Always observe good personal hygie and before eating, drinking, and/or se equipment to remove contaminants. workplace.	moking. Routinely wash work c	lothing and protective
vironmental exposure ntrols	Inform appropriate managerial or sup from ventilation or work process equi requirements of environmental protect modifications to the process equipment levels.	pment should be checked to en ction legislation. Fume scrubber	nsure they comply with the rs, filters or engineering
	chemical properties		

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Form	Liquid.
Color	Grey.
Odor	Slight.
Melting point/freezing point	Not available.

Boiling point or initial boiling point and boiling range	>400 °F (>204,44 °C)	
Flammability	Not applicable.	
Flash point	>400,0 °F (>204,4 °C) Pensky-Martens Closed Cup	
Auto-ignition temperature	Not available.	
Decomposition temperature	Not available.	
рН	Not available.	
Kinematic viscosity	Not available.	
Solubility		
Solubility (water)	Not available.	
Partition coefficient (n-octanol/water) (log value)	Not available.	
Vapor pressure	Not available.	
Density and/or relative density		
Density	1,96 g/cm3	
Vapor density	>1	
Particle characteristics	Not available.	
9.2. Other information		
9.2.1. Information with regard to physical hazard classes	No relevant additional information available.	
9.2.2. Other safety characteristics		
Evaporation rate	<1	
Specific gravity	1,96	
SECTION 10: Stability and reactivity		
10.1. Reactivity	The product is stable and non-reactive under normal conditio	
10.2. Chemical stability	Material is stable under normal conditions.	
	No development of the law source development it is a set of the source o	

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidizing agents.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11: Toxicological information

Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

General information

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
Symptoms	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Species	Test Results
Guinea pig	5640 mg/kg
Rat	> 2680 mg/m3, 4 Hours
Rat	1540 mg/kg
	Guinea pig Rat

Components	Species	Test Results	
CARBON BLACK (CAS 1333-86-4	4)		
<u>Acute</u>			
Oral		"	
LD50	Rat	> 8000 mg/kg	
	ontaining 1 % or more of particle	s with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	
<u>Acute</u>			
Dermal LD50	Hamster	>= 10000 mg/kg	
	Tamsler	>= 10000 Hig/kg	
Oral LD50	Rat	> 10000 mg/kg	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye irritation	Causes serious eye irritation.		
Respiratory sensitization	Due to partial or complete lack	of data the classification is not possible.	
Skin sensitization	May cause an allergic skin rea	ction.	
Germ cell mutagenicity	No data available to indicate p mutagenic or genotoxic.	roduct or any components present at greater than 0.1% are	
Carcinogenicity	Not classified.		
	nance on protection against a	nd preventing risk relating to exposure to carcinogens at work	
titanium dioxide [in powde	er form containing 1 % or more c Evaluation of Carcinogenicity	f particles with aerodynamic diameter \leq 10 µm] (CAS 13463-67-7)	
Butyrolactone (CAS 96-4 CARBON BLACK (CAS 1 Crystalline SiO2 (Quartz)	8-0) 1333-86-4) (CAS 14808-60-7) er form containing 1 % or more	3 Not classifiable as to carcinogenicity to humans.2B Possibly carcinogenic to humans.1 Carcinogenic to humans.2B Possibly carcinogenic to humans.	
Reproductive toxicity	This product is not expected to	cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure		of data the classification is not possible.	
Specific target organ toxicity - repeated exposure	Due to partial or complete lack	of data the classification is not possible.	
Aspiration hazard	Due to partial or complete lack of data the classification is not possible.		
Mixture versus substance information	No information available.		
11.2. Information on other hazar	rde		
Endocrine disrupting properties	This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.		
Other information	Not available.		
SECTION 12: Ecological i	nformation		
12.1. Toxicity	Toxic to aquatic life with long l	asting effects.	
12.2. Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.		
12.3. Bioaccumulative potential			
Partition coefficient n-octanol/water (log Kow) Butyrolactone		-0,64	
Bioconcentration factor (BCF)	Not available.		
	No data available.		
12.4. Mobility in soil	No data available.		

12.6. Endocrine disrupting properties	This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.
12.7. Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations


13.1. Waste treatment methods	
Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

	14.1. UN number	
	14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin:reaction Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin))
	14.3. Transport hazard class(
	Class	9
	Subsidiary risk	-
	Label(s)	9
	Hazard No. (ADR)	90
	Tunnel restriction code	E
	14.4. Packing group	
	14.5. Environmental hazards	No.
	14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
	for user	
RID		
	14.1. UN number	UN3082
	14.2. UN proper shipping	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin:reaction
	name	Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin))
	14.3. Transport hazard class((es)
	Class	9
	Subsidiary risk	-
	Label(s)	9
	14.4. Packing group	III
	14.5. Environmental hazards	
	14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
	for user	
ADI	-	
	14.1. UN number	UN3082
	14.2. UN proper shipping	Environmentally Hazardous Liquid, N.o.s. (Epoxy Resin:reaction Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin))
	name	
	14.3. Transport hazard class(
	Class	9
	Subsidiary risk	9
	Label(s) 14.4. Packing group	
	14.5. Environmental hazards	
	14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
	for user	rida daloty indiadiono, obo and omorgonoy proceduros soloro nanaling.
IAT		
-	14.1. UN number	UN3082
	14.2. UN proper shipping	Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin:reaction Product Of
	name	Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin))

14.3. Transport hazard class	(es)
Class	9
Subsidiary risk	-
14.4. Packing group	
14.5. Environmental hazards	No.
ERG Code	9L
14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
for user	
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
14.1. UN number	UN3082
14.2. UN proper shipping	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin:reaction
name	Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)), MARINE POLLUTANT
14.3. Transport hazard class	(es)
Class	9
Subsidiary risk	-
14.4. Packing group	
14.5. Environmental hazards	
Marine pollutant	Yes
EmS	F-A, S-F
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
14.7. Maritime transport in bulk according to IMO instruments	Not established.



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended CARBON BLACK (CAS 1333-86-4)

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 µm] (CAS 13463-67-7) Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

UFI:

Austria: H050-60UJ-A00F-6JWE Belgium: H050-60UJ-A00F-6JWE Bulgaria: H050-60UJ-A00F-6JWE Croatia: H050-60UJ-A00F-6JWE Cyprus: H050-60UJ-A00F-6JWE Czech Republic: H050-60UJ-A00F-6JWE Denmark: H050-60UJ-A00F-6JWE Estonia: H050-60UJ-A00F-6JWE EU: H050-60UJ-A00F-6JWE Finland: H050-60UJ-A00F-6JWE France: H050-60UJ-A00F-6JWE Germany: H050-60UJ-A00F-6JWE Greece: H050-60UJ-A00F-6JWE Hungary: H050-60UJ-A00F-6JWE Iceland: H050-60UJ-A00F-6JWE Ireland: H050-60UJ-A00F-6JWE Italy: H050-60UJ-A00F-6JWE Latvia: H050-60UJ-A00F-6JWE Lithuania: H050-60UJ-A00F-6JWE Luxembourg: H050-60UJ-A00F-6JWE Malta: H050-60UJ-A00F-6JWE Netherlands: H050-60UJ-A00F-6JWE Norway: H050-60UJ-A00F-6JWE Poland: H050-60UJ-A00F-6JWE Portugal: H050-60UJ-A00F-6JWE Romania: H050-60UJ-A00F-6JWE Slovakia: H050-60UJ-A00F-6JWE Slovenia: H050-60UJ-A00F-6JWE Spain: H050-60UJ-A00F-6JWE Sweden: H050-60UJ-A00F-6JWE

Authorizations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Restrictions on use

Not listed.

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered

Not listed.

(CAS 13463-67-7)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Crystalline SiO2 (Quartz) (CAS 14808-60-7)

Other EU regulations	Directive 2012/18/EU on majo	r accident hazards involving dangerous substances, as amended
	ANNEX 1, PART 1 Categories Hazard categories in accordar - E2 Hazardous to the Aquatic	nce with Regulation (EC) No 1272/2008
Other regulations	1	abelled in accordance with Regulation (EC) 1272/2008 (CLP Safety Data Sheet complies with the requirements of Regulation led.
National regulations	Directive 94/33/EC on the prot	old are not allowed to work with this product according to EU ection of young people at work, as amended. Follow national cal agents in accordance with Directive 98/24/EC, as amended.
Contains a substance whic toxic substances	h is included on the TRGS 905	list of carcinogenic, germ cell mutagenic and reproductive
CARBON BLACK (CAS 1333-86-4)		Anorganische Faserstäube, soweit nicht erwähnt (ausgenommen Gipsfasernund Wollastonitfasern)
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 µm]		Anorganische Faserstäube, soweit nicht erwähnt (ausgenommen Gipsfasernund Wollastonitfasern)

France regulations

France INRS Table of Occupational Diseases

Crystalline SiO2 (Quartz) (CAS 14808-60-7)

Epoxy Resin: Reaction product of bisphenol A and epichlorohydrin (refer to epichlorohydrin) (CAS 25068-38-6)

Product registration number

Austria	UFI: H050-60UJ-A00F-6JWE
Belgium	UFI: H050-60UJ-A00F-6JWE
Czech Republic	UFI: H050-60UJ-A00F-6JWE
Denmark	UFI: H050-60UJ-A00F-6JWE
European Union	UFI: H050-60UJ-A00F-6JWE
Finland	UFI: H050-60UJ-A00F-6JWE
France	UFI: H050-60UJ-A00F-6JWE
Germany	UFI: H050-60UJ-A00F-6JWE
Greece	UFI: H050-60UJ-A00F-6JWE
Hungary	UFI: H050-60UJ-A00F-6JWE
Italy	UFI: H050-60UJ-A00F-6JWE
Netherlands	UFI: H050-60UJ-A00F-6JWE
Norway	UFI: H050-60UJ-A00F-6JWE
Poland	UFI: H050-60UJ-A00F-6JWE
Portugal	UFI: H050-60UJ-A00F-6JWE
Slovakia	UFI: H050-60UJ-A00F-6JWE
Slovenia	UFI: H050-60UJ-A00F-6JWE
Spain	UFI: H050-60UJ-A00F-6JWE
Sweden	UFI: H050-60UJ-A00F-6JWE
Switzerland	UFI: H050-60UJ-A00F-6JWE
15.2. Chemical safety assessment	No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

	ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.
	ADR: Agreement concerning the International Carriage of Dangerous Goods by Road. AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany). CAS: Chemical Abstract Service.
	CEN: European Committee for Standardization.
	IATA: International Air Transport Association.
	IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.
	IMDG: International Maritime Dangerous Goods.
	MAC: Maximum Allowed Concentration.
	MARPOL: International Convention for the Prevention of Pollution from Ships.
	PBT: Persistent, bioaccumulative and toxic.
	RID: Regulations concerning the International Carriage of Dangerous Goods by Rail. STEL: Short term exposure limit.
	TLV: Threshold Limit Value.
	TWA: Time Weighted Average.
	VLE: Exposure Limit Value.
	VME: Exposure Average Value.
	vPvB: Very persistent and very bioaccumulative.
References	Not available.
Information on evaluation method leading to the classification of mixture	The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.
Full text of any statements, which are not written out in full	
under sections 2 to 15	H302 Harmful if swallowed.
	H315 Causes skin irritation.
	H317 May cause an allergic skin reaction.
	H319 Causes serious eye irritation.
	H331 Toxic if inhaled.
	H350 May cause cancer.

Affections consécutives à l'inhalation de poussières minérales renfermant de la silicecristalline (quartz, cristobalite, tridymite), des silicates cristallins (kaolin, talc), du graphite ou de la houille 25

Maladies professionnelles provoquées par les résines époxydiques et leurs constituants 51 Revision information Training information Disclaimer H351 Suspected of causing cancer. None.

Follow training instructions when handling this material.

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.