SAFETY DATA SHEET

Version #: 07

Issue date: 05-28-2019 Revision date: 07-26-2023 Supersedes date: 07-13-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

of the mixture

DEVCON® Bronze Putty (BR) Resin

Registration number

Synonyms None.
SKU# 0134

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Not available.

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company Name ITW Performance Polymers

Address Bay 150

Shannon Industrial Estate

Co. Clare Ireland V14 DF82

Contact Person Customer Service
Telephone Number 353(61)771500

353(61)471285

Email customerservice.shannon@itwpp.com

Emergency Phone Number 44(0) 1235 239 670 (24 hours)

1.4. Emergency telephone number

General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

Austria National Poisons Information Center

+431 406 4343 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Belgium National Poisons

Control Center

070 245 245 (Available 24 hours a day. SDS/Product information may not be

Bulgaria National

available for the Emergency Service.)

Toxicological Information

Center

+359 2 9154 233 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Croatia Poisons Information Center

+385 1 2348 342 (Hours of operation not provided. SDS/Product information may

not be available for the Emergency Service.)

Cyprus Poison Center 1401 (Available 24 hours a day. SDS/Product information may not be available

for the Emergency Service.)

Czech Republic National Poisons Information

Center

+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Denmark National Poisons

Control Center

+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Estonia National Poisons Information Center

16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be

available for the Emergency Service.)

Finland National Poison Information Center

(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Material name: DEVCON® Bronze Putty (BR) Resin
0134 Version #: 07 Revision date: 07-26-2023 Issue date: 05-28-2019

1.4. Emergency telephone number

France National Poisons
Control Center

ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Greece Poison Information

Centre

(0030) 2107793777 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Hungary National

Iceland Poison Center

Emergency Phone Number

+36-80-201-199 (Available 24 hours a day. SDS/Product information may not be

(+354) 543 2222 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

available for the Emergency Service.)

Latvia Emergency medical

aid

Latvia Poison and Drug Information Center +371 67042473 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Lithuania Neatidėliotina informacija apsinuodijus

+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Malta Accident and Emergency Department 2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Netherlands National Poisons Information Center (NVIC) NVIC: +31 (0)88 755 8000 (Only for the purpose of informing medical personnel in cases of acute intoxications)

--- 00 50 40 00

Norway Norwegian Poison Information Center

22 59 13 00 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Portugal Poison Center

800 250 250 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Romania Biroul RSI si Informare Toxicologica 021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be available for the Emergency Service.)

Slovakia National Toxicological Information +421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Center
Spain Toxicology

+ 34 91 562 04 20 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Sweden National Poison Information Center

112 - and ask for Poison Information (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Switzerland Tox Info

Information Service

145 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Suisse

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Skin corrosion/irritation Category 2 H315 - Causes skin irritation.
Serious eye damage/eye irritation Category 2 H319 - Causes serious eye

irritation.

Skin sensitization Category 1 H317 - May cause an allergic skin

reaction.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

UFI:

Austria: V410-E0SP-J006-E6PH Belgium: V410-E0SP-J006-E6PH Bulgaria: V410-E0SP-J006-E6PH Croatia: V410-E0SP-J006-E6PH Cyprus: V410-E0SP-J006-E6PH

Czech Republic: V410-E0SP-J006-E6PH Denmark: V410-E0SP-J006-E6PH Estonia: V410-E0SP-J006-E6PH EU: V410-E0SP-J006-E6PH Finland: V410-E0SP-J006-E6PH France: V410-E0SP-J006-E6PH Germany: V410-E0SP-J006-E6PH Greece: V410-E0SP-J006-E6PH Hungary: V410-E0SP-J006-E6PH Iceland: V410-E0SP-J006-E6PH Ireland: V410-E0SP-J006-E6PH Italy: V410-E0SP-J006-E6PH Latvia: V410-E0SP-J006-E6PH Lithuania: V410-E0SP-J006-E6PH Luxembourg: V410-E0SP-J006-E6PH Malta: V410-E0SP-J006-E6PH Netherlands: V410-E0SP-J006-E6PH Norway: V410-E0SP-J006-E6PH Poland: V410-E0SP-J006-E6PH Portugal: V410-E0SP-J006-E6PH Romania: V410-E0SP-J006-E6PH Slovakia: V410-E0SP-J006-E6PH Slovenia: V410-E0SP-J006-E6PH

Spain: V410-E0SP-J006-E6PH Sweden: V410-E0SP-J006-E6PH

Contains: Epoxy Resin: reaction product of Bisphenol A and epichlorohydrin (refer to epichlorohydrin)

Hazard pictograms



Signal word Warning

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Precautionary statements

Prevention

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear eye protection/face protection.

P280 Wear protective gloves.

Response

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage Not available.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information None.

2.3. Other hazards This

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name % CAS-No. / EC No. REACH Registration No. **Notes** Index No. granulated copper; [particle length: 30 - 607440-50-8 029-024-00-X 231-159-6 from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] Classification: Acute Tox. 4;H302;(ATE: 500 mg/kg bw), Acute Tox. 3;H331;(ATE: 0,73 mg/l), Eye Irrit. 2;H319, Aquatic Acute 1;H400(M=10), Aquatic Chronic 1;H410(M=10) Epoxy Resin: reaction product of 10 - 30 25068-38-6 01-2119456619-26-0000 Bisphenol A and epichlorohydrin (refer to epichlorohydrin) Classification: Skin Irrit. 2;H315, Eye Irrit. 2;H319, Skin Sens. 1;H317 zinc powder — zinc dust (stabilised) 10 - 307440-66-6 030-001-01-9 231-175-3 Classification: Pyr. Sol. 1;H250, Self-heat. 2;H252, Water-React. 1;H260, Acute Tox. 4;H302;(ATE: 630 mg/kg bw), Aquatic Acute 1;H400, Aquatic Chronic 1;H410

Other components below reportable

5 - 10

levels

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Union workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and

delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis.

Rash.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

The unusual fire of explosion flazards floted

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting

procedures

Use water spray to cool unopened containers.

Specific methodsUse standard firefighting procedures and consider the hazards of other involved materials.

Material name: DEVCON® Bronze Putty (BR) Resin

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency Do not touch damaged containers or spilled material unless wearing appropriate protective

clothing. Do not touch or walk through spilled material. personnel

Keep unnecessary personnel away. Ensure adequate ventilation. Local authorities should be For emergency responders

advised if significant spillages cannot be contained. Use personal protection recommended in

Section 8 of the SDS.

6.2. Environmental precautions Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Following product recovery, flush area

with water.

Small Spills: Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing.

Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the

SDS).

7.3. Specific end use(s) Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, O	DEL Ordinance	(GwV), BGBI.	II, no. 184/2	2001, as amended
----------------------	---------------	--------------	---------------	------------------

Components	Туре	Value	Form
granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8)	MAK	1 mg/m3	Inhalable fraction.
		0,1 mg/m3	Fume and respirable dust.
	STEL	4 mg/m3	Inhalable fraction.
		0,4 mg/m3	Fume and respirable dust.

Belgium. OEL. Exposure Limit Values to Chemical Substances at Work, Code of Well-being at work, Book VI, Title 1 -Chemical agents, as amended

Components	Туре	Value	Form	
granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8)	TWA	1 mg/m3	Dust and mist.	
		0.2 mg/m3	Fume.	

Bulgaria. OELs. Ordinance No 13 on protection of workers against risks of exposure to chemical agents at work, as amended

Components	Туре	Value	
granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8)	TWA	0,1 mg/m3	

Material name: DEVCON® Bronze Putty (BR) Resin

Croatia. OELs (GVI). Regulation on Protection of Workers against Exposure to Dangerous Chemicals at Work, OELs and Biological Limit Values, Annex I (NN 91/2018), as amended Components **Type** Value **Form** granulated copper; [particle MAC 1 mg/m3 length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) 0,2 mg/m3 Dust. STEL 2 mg/m3 Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended Components Value Form Type granulated copper; [particle TWA 0,2 mg/m3 Fume. length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Czech Republic. Occupational exposure limit values of chemicals at work (Decree on protection of health at work, 361/2007, Annex 2, Part A & Annex 3, Part A, as amended) Form Components Value Type granulated copper; [particle Ceiling 2 mg/m3 Aerosol, inhalable. length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Respirable aerosol 0,2 mg/m3 fraction TWA Aerosol, inhalable, 1 mg/m3 Respirable aerosol $0,1 \, \text{mg/m}3$ fraction Denmark. Work Environment Authority. Exposure Limits for Substances & Materials, Annex 2 Components Value **Form Type** TLV granulated copper; [particle Dust. 1 mg/m3 length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) 0,1 mg/m3 Fume. Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended Components Value Form Type TWA granulated copper; [particle 1 mg/m3 Total dust. length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) 0,2 mg/m3 Fine dust.

Finland. HTP-arvot, App 3., Binding Limit Values, Social Affairs and Ministry of Health **Form** Components **Type** Value granulated copper; [particle **TWA** 0,02 mg/m3 Respirable. length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) 0,02 mg/m3 Respirable dust and/or fume.

Components	alues (VLEP) for Occupational Expos Type	Value	Form
granulated copper; [particle ength: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8)	VLE	2 mg/m3	Dust.
•	ndicative limit (VL)		
	VME	1 mg/m3	Dust.
Regulatory status:	ndicative limit (VL)	0,2 mg/m3	Fume.
Regulatory status:	ndicative limit (VL)		
Germany. DFG MAK List (n the Work Area (DFG), as	advisory OELs). Commission for the	Investigation of Health Hazard	ls of Chemical Compounds
Components	туре Туре	Value	Form
granulated copper; [particle ength: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8)	TWA	0,01 mg/m3	Respirable fraction.
zinc powder — zinc dust stabilised) (CAS 7440-66-6)	TWA	2 mg/m3	Inhalable fraction.
		0,1 mg/m3	Respirable fraction.
Greece. OELs, Presidentia	Il Decree No. 307/1986, as amended		
Components	Туре	Value	Form
granulated copper; [particle ength: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8)	STEL	2 mg/m3	Dust.
,	TWA	1 mg/m3	Dust.
		0,2 mg/m3	Fume.
lungary. OELs. Decree or	n protection of workers exposed to ch	nemical agents (5/2020. (II.6)),	Annex 1&2, as amended
Components	Туре	Value	
granulated copper; [particle ength: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8)	STEL	0,2 mg/m3	
celand. OELs. Regulation Components	390/2009 on Pollution Limits and Me Type	asures to Reduce Pollution at Value	the Workplace, as amende Form
granulated copper; [particle ength: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8)	TWA	1 mg/m3	Total dust.
•		0,1 mg/m3	Respirable dust.
reland. OELVs, Schedule: Components	s 1 & 2, Code of Practice for Chemica Type	l Agents and Carcinogens Reg Value	gulations Form
granulated copper; [particle ength: from 0,9 mm to 6,0 nm; particle width: from 0,494 to 0,949 mm] (CAS	TWA	1 mg/m3	Dust and mist.
7440-50-8)		0,2 mg/m3	Fume.

Components	Туре	Value	Form
ranulated copper; [particle ength: from 0,9 mm to 6,0 nm; particle width: from ,494 to 0,949 mm] (CAS 440-50-8)	TWA	1 mg/m3	Dust and mist.
,		0,2 mg/m3	Fume.
atvia. OELs. Occupational Exposi	ure Limits of Chemical Substa	nces at Workplace (Reg. No.	. 325/ 2007, L.V. 80, Anne
), as amended Components	Туре	Value	
•	STEL		
ranulated copper; [particle ength: from 0,9 mm to 6,0 nm; particle width: from 1,494 to 0,949 mm] (CAS 1440-50-8)	SIEL	1 mg/m3	
,	TWA	0,5 mg/m3	
.ithuania. OELs. Occupational Exp /-824/A1-389), as amended	osure Limit Values for Chemi	cal Substances (Hygiene No	rm HN 23:2011; Order No
Components	Туре	Value	Form
granulated copper; [particle ength: from 0,9 mm to 6,0 nm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8)	TWA	1 mg/m3	Inhalable fraction.
		0,2 mg/m3	Respirable fraction.
letherlands. OELs per Annex XIII o	of Working Conditions Regula	tion (Staatscourant no. 252,	29 December 2006), as
imended Components	Туре	Value	Form
granulated copper; [particle	TWA	0,1 mg/m3	Inhalable fraction.
ength: from 0,9 mm to 6,0		o, ig/o	minalable maedem
nm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8)			
nm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Norway. Regulation No. 1358 on M		Physical and Chemical Facto	ors in Work Environment
nm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Norway. Regulation No. 1358 on Monfection Groups for Biological Fac	tors, as amended	Physical and Chemical Facto	ers in Work Environment Form
nm; particle width: from 1,494 to 0,949 mm] (CAS 1,440-50-8) Horway. Regulation No. 1358 on Monfection Groups for Biological Fac Components	tors, as amended Type	Value	
nm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Norway. Regulation No. 1358 on Monfection Groups for Biological Factory and the components pranulated copper; [particle ength: from 0,9 mm to 6,0 nm; particle width: from 0,494 to 0,949 mm] (CAS	tors, as amended	•	Form
nm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Norway. Regulation No. 1358 on Monfection Groups for Biological Factory and the components of the components of the component of the	tors, as amended Type	Value	Form
nm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Norway. Regulation No. 1358 on Monfection Groups for Biological Factory and the following for Biological Factory and the following for Biological Factory and the following form 0,9 mm to 6,0 nm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Poland. Maximum permissible con	etors, as amended Type TLV	Value 1 mg/m3 0,1 mg/m3	Form Dust. Fume.
nm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Norway. Regulation No. 1358 on Monfection Groups for Biological Factomponents granulated copper; [particle ength: from 0,9 mm to 6,0 nm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Poland. Maximum permissible con 1286/2018, Annex 1)	etors, as amended Type TLV	Value 1 mg/m3 0,1 mg/m3	Form Dust. Fume.
nm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Norway. Regulation No. 1358 on M	etors, as amended Type TLV centrations and intensities of	Value 1 mg/m3 0,1 mg/m3 harmful factors in the work of	Form Dust. Fume.
nm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Norway. Regulation No. 1358 on Monfection Groups for Biological Factory Components granulated copper; [particle ength: from 0,9 mm to 6,0 nm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Poland. Maximum permissible con 1286/2018, Annex 1) Components granulated copper; [particle ength: from 0,9 mm to 6,0 nm; particle width: from 0,9 mm to 6,0 nm; particle width: from 0,494 to 0,949 mm] (CAS	ctors, as amended Type TLV centrations and intensities of	Value 1 mg/m3 0,1 mg/m3 harmful factors in the work of Value	Form Dust. Fume.
nm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Norway. Regulation No. 1358 on Monfection Groups for Biological Factomponents granulated copper; [particle ength: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Poland. Maximum permissible con 1286/2018, Annex 1) Components granulated copper; [particle ength: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Portugal. VLEs. Norm on occupation	ctors, as amended Type TLV centrations and intensities of Type TWA	Value 1 mg/m3 0,1 mg/m3 harmful factors in the work of Value 0,2 mg/m3 ents (NP 1796-2014)	Form Dust. Fume. environment (Dz.U.Poz.
nm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Norway. Regulation No. 1358 on Monfection Groups for Biological Factomponents Granulated copper; [particle ength: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Poland. Maximum permissible con 1286/2018, Annex 1) Components Granulated copper; [particle ength: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Portugal. VLEs. Norm on occupation components	ctors, as amended Type TLV centrations and intensities of Type TWA onal exposure to chemical age Type	Value 1 mg/m3 0,1 mg/m3 harmful factors in the work of Value 0,2 mg/m3 ents (NP 1796-2014) Value	Form Dust. Fume. environment (Dz.U.Poz.
nm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Norway. Regulation No. 1358 on Monfection Groups for Biological Factomponents granulated copper; [particle ength: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Poland. Maximum permissible con 1286/2018, Annex 1) Components granulated copper; [particle ength: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Portugal. VLEs. Norm on occupation	ctors, as amended Type TLV centrations and intensities of Type TWA	Value 1 mg/m3 0,1 mg/m3 harmful factors in the work of Value 0,2 mg/m3 ents (NP 1796-2014)	Form Dust. Fume. environment (Dz.U.Poz.

amended) Components	Туре	Value	Form
granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8)	STEL	1,5 mg/m3	Dust.
		0,2 mg/m3	Fume.
	TWA	0,5 mg/m3	Dust.
Slovakia. OELs. Maximum p Annex 1, Table 1, as amend	permissible exposure limits for chem	ical factors in workplace air (Regulation No 355/2006,
Components	Туре	Value	Form
granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8)	TWA	1 mg/m3	Inhalable fraction.
		0,2 mg/m3	Respirable fume.
zinc powder — zinc dust (stabilised) (CAS 7440-66-6)	TWA	2 mg/m3	Inhalable fraction.
/		0,1 mg/m3	Respirable fraction.
Spain. OELs. INSST. Límite	s de Exposición Profesional Para Ag	entes Químicos. Table 1-Valo	ores Límites Ambientales
(VLAs)	-		
Components granulated copper; [particle	Type TWA	Value 0,1 mg/m3	Form Respirable fraction.
length: from 0,9 mm to 6,0 mm; particle width: from			
amended	Vork Environment Authority (AV), Oc		
7440-50-8) Sweden. OELs (Annex 1). V	Vork Environment Authority (AV), Occ	cupational Exposure Limit Va Value	ilues (AFS 2018:1), as Form
7440-50-8) Sweden. OELs (Annex 1). Wamended			
7440-50-8) Sweden. OELs (Annex 1). Wamended Components granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8)	Туре	Value 0,01 mg/m3	Form
7440-50-8) Sweden. OELs (Annex 1). Wamended Components granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Switzerland. SUVA Grenzwe Components granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS	Type TWA erte am Arbeitsplatz: Aktuelle MAK-W	Value 0,01 mg/m3 /erte	Form Respirable dust.
7440-50-8) Sweden. OELs (Annex 1). Wamended Components granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Switzerland. SUVA Grenzwe Components granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from	Type TWA erte am Arbeitsplatz: Aktuelle MAK-W Type	Value 0,01 mg/m3 /erte Value	Form Respirable dust. Form
7440-50-8) Sweden. OELs (Annex 1). Wamended Components granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Switzerland. SUVA Grenzwe Components granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8)	Type TWA erte am Arbeitsplatz: Aktuelle MAK-W Type STEL TWA	Value 0,01 mg/m3 Value Value 0,2 mg/m3 0,1 mg/m3	Form Form Inhalable fraction.
7440-50-8) Sweden. OELs (Annex 1). Wamended Components granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Switzerland. SUVA Grenzwe Components granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8)	Type TWA erte am Arbeitsplatz: Aktuelle MAK-W Type STEL	Value 0,01 mg/m3 Value Value 0,2 mg/m3 0,1 mg/m3	Form Form Inhalable fraction.
7440-50-8) Sweden. OELs (Annex 1). Wamended Components granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Switzerland. SUVA Grenzwe Components granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) UK. OELs. Workplace Expo	Type TWA erte am Arbeitsplatz: Aktuelle MAK-W Type STEL TWA sure Limits (WELs) (EH40/2005 (Four	Value 0,01 mg/m3 Verte Value 0,2 mg/m3 0,1 mg/m3 th Edition 2020)), Table 1	Form Form Inhalable fraction. Form
7440-50-8) Sweden. OELs (Annex 1). Wamended Components granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Switzerland. SUVA Grenzwe Components granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) UK. OELs. Workplace Expo Components granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7494 to 0,949 mm] (CAS 7495 mm)	Type TWA erte am Arbeitsplatz: Aktuelle MAK-W Type STEL TWA TWA sure Limits (WELs) (EH40/2005 (Four	Value 0,01 mg/m3 Verte Value 0,2 mg/m3 0,1 mg/m3 th Edition 2020)), Table 1 Value	Form Form Inhalable fraction. Form Inhalable dusts and miss
7440-50-8) Sweden. OELs (Annex 1). Wamended Components granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Switzerland. SUVA Grenzwe Components granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) UK. OELs. Workplace Expo Components granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7494 to 0,949 mm] (CAS 7495 mm)	Type TWA erte am Arbeitsplatz: Aktuelle MAK-W Type STEL TWA sure Limits (WELs) (EH40/2005 (Four Type STEL	Value 0,01 mg/m3 Verte Value 0,2 mg/m3 0,1 mg/m3 th Edition 2020)), Table 1 Value 2 mg/m3	Form Form Inhalable fraction. Form Inhalable dusts and miss
7440-50-8) Sweden. OELs (Annex 1). Wamended Components granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Switzerland. SUVA Grenzwe Components granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) UK. OELs. Workplace Expo Components granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7494 to 0,949 mm] (CAS 7495 mm)	Type TWA erte am Arbeitsplatz: Aktuelle MAK-W Type STEL TWA sure Limits (WELs) (EH40/2005 (Four Type STEL	Value 0,01 mg/m3 Verte Value 0,2 mg/m3 0,1 mg/m3 th Edition 2020)), Table 1 Value 2 mg/m3 1 mg/m3 0,2 mg/m3	Form Form Inhalable fraction. Form Inhalable dusts and mist
7440-50-8) Sweden. OELs (Annex 1). Wamended Components granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) Switzerland. SUVA Grenzwe Components granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) UK. OELs. Workplace Expo Components granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8)	Type TWA erte am Arbeitsplatz: Aktuelle MAK-W Type STEL TWA esure Limits (WELs) (EH40/2005 (Four Type STEL	Value 0,01 mg/m3 Verte Value 0,2 mg/m3 0,1 mg/m3 th Edition 2020)), Table 1 Value 2 mg/m3 1 mg/m3 0,2 mg/m3 or the ingredient(s).	Form Form Inhalable fraction. Form Inhalable dusts and mist

Predicted no effect concentrations (PNECs)

Not available.

8.2. Exposure controls

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

- Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to

acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid.

Form Solid. Paste.
Color Bronze.
Odor Slight.

Melting point/freezing point Not available.

Boiling point or initial boiling

point and boiling range

608 °F (320 °C) estimated

Flammability Not available.

Flash point >399,9 °F (>204,4 °C)

265,0 °F (129,4 °C) estimated

Auto-ignition temperatureNot available.Decomposition temperatureNot available.pHNot available.Kinematic viscosityNot available.

Solubility

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water) (log value)

Vapor pressure Not available.

Density and/or relative density

Density2,60 g/cm3Vapor densityNot available.Particle characteristicsNot available.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No relevant additional information available.

9.2.2. Other safety characteristics

Specific gravity 2,6

SECTION 10: Stability and reactivity

10.1. ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stabilityMaterial is stable under normal conditions

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoidContact with incompatible materials.

10.5. Incompatible materials Strong oxidizing agents.

10.6. Hazardous

decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation No adverse effects due to inhalation are expected.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Not known.

Components Species Test Results

zinc powder — zinc dust (stabilised) (CAS 7440-66-6)

Acute Oral

LD50 Rat 630 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory sensitizationDue to partial or complete lack of data the classification is not possible.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible.

Reproductive toxicity

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity
Due to partial or complete lack of data the classification is not possible.

single exposure

Specific target organ toxicity -

Due to partial or complete lack of data the diacomoditor to het peccible.

reported expenses

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Aspiration hazard Due to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

No information available.

11.2. Information on other hazards

Endocrine disrupting

properties

This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than

0.1% by weight.

Other information Not available.

SECTION 12: Ecological information

12.1. ToxicityBased on available data, the classification criteria are not met for hazardous to the aquatic

environment.

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential No data available.

Material name: DEVCON® Bronze Putty (BR) Resin

Partition coefficient

n-octanol/water (log Kow)

Not available.

Bioconcentration factor (BCF)

Not available. No data available.

12.4. Mobility in soil

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII.

12.6. Endocrine disrupting

properties

This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than

0.1% by weight.

12.7. Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

12.8. Additional information

Estonia Dangerous substances in soil Data

granulated copper; [particle length: from 0,9 mm to 6,0

mm; particle width: from 0,494 to 0,949 mm]

(CAS 7440-50-8)

Copper (Cu) 100 MG/KG

Copper (Cu) 150 MG/KG Copper (Cu) 500 MG/KG

zinc powder — zinc dust (stabilised) (CAS 7440-66-6)

Zinc (Zn) 1000 MG/KG Zinc (Zn) 200 MG/KG Zinc (Zn) 500 MG/KG

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

The Waste code should be assigned in discussion between the user, the producer and the waste EU waste code

disposal company.

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of Disposal methods/information

contents/container in accordance with local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number Not regulated as dangerous goods.

14.2. UN proper shipping

Not regulated as dangerous goods.

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary risk

Hazard No. (ADR) Not assigned. **Tunnel restriction code** Not assigned.

14.4. Packing group 14.5. Environmental hazards No.

14.6. Special precautions

for user

Not assigned.

RID

14.1. UN number 14.2. UN proper shipping Not regulated as dangerous goods.

Not regulated as dangerous goods.

name

14.3. Transport hazard class(es)

Not assigned. Class

Subsidiary risk 14.4. Packing group 14.5. Environmental hazards No.

Not assigned. 14.6. Special precautions

for user

ΔDN

14.1. UN number Not regulated as dangerous goods. **14.2. UN proper shipping** Not regulated as dangerous goods.

name

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary risk 14.4. Packing group 14.5. Environmental hazards No.

14.6. Special precautions Not assigned.

for user

IATA

14.1. UN number Not regulated as dangerous goods.14.2. UN proper shipping Not regulated as dangerous goods.

name

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary risk -14.4. Packing group -14.5. Environmental hazards No.

14.6. Special precautions Not assigned.

for user

IMDG

14.1. UN number Not regulated as dangerous goods.14.2. UN proper shipping Not regulated as dangerous goods.

name

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary risk 14.4. Packing group 14.5. Environmental hazards
Marine pollutant No.

EmS Not assigned. 14.6. Special precautions Not assigned.

for user

14.7. Maritime transport in bulk Not applicable.

according to IMO instruments

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

granulated copper; [particle length: from 0,9 mm to 6,0 mm; particle width: from 0,494 to 0,949 mm] (CAS 7440-50-8) zinc powder — zinc dust (stabilised) (CAS 7440-66-6)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Material name: DEVCON® Bronze Putty (BR) Resin

UFI:

Austria: V410-E0SP-J006-E6PH Belgium: V410-E0SP-J006-E6PH Bulgaria: V410-E0SP-J006-E6PH Croatia: V410-E0SP-J006-E6PH Cyprus: V410-E0SP-J006-E6PH

Czech Republic: V410-E0SP-J006-E6PH Denmark: V410-E0SP-J006-E6PH Estonia: V410-E0SP-J006-E6PH EU: V410-E0SP-J006-E6PH Finland: V410-E0SP-J006-E6PH France: V410-E0SP-J006-E6PH Germany: V410-E0SP-J006-E6PH Greece: V410-E0SP-J006-E6PH Hungary: V410-E0SP-J006-E6PH Iceland: V410-E0SP-J006-E6PH Ireland: V410-E0SP-J006-E6PH Italy: V410-E0SP-J006-E6PH Latvia: V410-E0SP-J006-E6PH Lithuania: V410-E0SP-J006-E6PH Luxembourg: V410-E0SP-J006-E6PH Malta: V410-E0SP-J006-E6PH Netherlands: V410-E0SP-J006-E6PH Norway: V410-E0SP-J006-E6PH Poland: V410-E0SP-J006-E6PH Portugal: V410-E0SP-J006-E6PH Romania: V410-E0SP-J006-E6PH Slovakia: V410-E0SP-J006-E6PH Slovenia: V410-E0SP-J006-E6PH

Spain: V410-E0SP-J006-E6PH Sweden: V410-E0SP-J006-E6PH

Authorizations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Not listed.

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

National regulations

Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended. Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

France regulations

France INRS Table of Occupational Diseases

Epoxy Resin: reaction product of Bisphenol A and epichlorohydrin (refer to epichlorohydrin)

époxydiques et leurs constituants 51

Maladies professionnelles provoquées par les résines

(CAS 25068-38-6)

Product registration number

UFI: V410-E0SP-J006-E6PH **Austria Belgium** UFI: V410-E0SP-J006-E6PH **Czech Republic** UFI: V410-E0SP-J006-E6PH **Denmark** UFI: V410-E0SP-J006-E6PH **European Union** UFI: V410-E0SP-J006-E6PH **Finland** UFI: V410-E0SP-J006-E6PH UFI: V410-E0SP-J006-E6PH **France** Germany UFI: V410-E0SP-J006-E6PH Greece UFI: V410-E0SP-J006-E6PH Hungary UFI: V410-E0SP-J006-E6PH UFI: V410-E0SP-J006-E6PH Italy **Netherlands** UFI: V410-E0SP-J006-E6PH Norway UFI: V410-E0SP-J006-E6PH **Poland** UFI: V410-E0SP-J006-E6PH UFI: V410-E0SP-J006-E6PH Portugal

Material name: DEVCON® Bronze Putty (BR) Resin

Slovakia UFI: V410-E0SP-J006-E6PH UFI: V410-E0SP-J006-E6PH Slovenia UFI: V410-E0SP-J006-E6PH Spain UFI: V410-E0SP-J006-E6PH Sweden UFI: V410-E0SP-J006-E6PH Switzerland

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland

Waterways.

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization. IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

Not available.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value.

vPvB: Very persistent and very bioaccumulative.

References

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements, which are not written out in full

under sections 2 to 15

H250 Catches fire spontaneously if exposed to air.

H252 Self-heating in large quantities; may catch fire.

H260 In contact with water releases flammable gases which may ignite spontaneously.

H302 Harmful if swallowed. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Revision information

Training information

Follow training instructions when handling this material.

Disclaimer

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Material name: DEVCON® Bronze Putty (BR) Resin